Schlumberger

BOREHOLE COMPENSATED SONIC LOG

| | |
|---|---|
| Company | MITCHELL ENERGY CORPORATION |
| Well | TL EXETER 11-9 |
| Field | WILDCAT |
| County | GALLIA |
| State | OHIO |
| Location | 1980' FSL & 1980' FEL |
| Sec. | 9 |
| Twp. | 4 NORTH |
| Rge. | 14 WEST |
| Permanent Datum | GROUND LEVEL |
| Elev. | 668 |
| Log Measured From | KELLY BUSHING |
| Drilling Measured From | KELLY BUSHING |
| Elev. K.B. | 688 |
| Elev. D.F. | 687 |
| Elev. G.L. | 668 |

Date Run One | 10-JUL-82
Depth Driller | 5222
Depth Logger | 5215
Bottom Logged Interval | 5210
Top Logged Interval | 1100
Type Fluid in Hole | GEL CHEM
Salinity, PPM Cl | 1000
Density / Viscosity | 9.2 / 38
pH / Fluid Loss | 10.5 / 6.4
Source of Sample | FLOWLINE
Rm @ Meas. Temp. | 1.52 @ 70°F
Rmf @ Meas. Temp. | 1.14 @ 70°F
Rmc @ Meas. Temp. | 2.28 @ 70°F
Source of Rmf / Rmc | MEASURED / CALCULATED
Rm @ BHT | 1.00 @ 120°F
Time Since Circulation | 12 HRS
Max. Rec. Temp. Deg. F | 120
Equipment Number | 5062-C
Location | GALLIA
Recorded By | D. SHEETS
Witnessed By | MR. MITCHELL

Run Number | ONE
Bit Size | 7 7/8"
Casing Driller Size | 5 1/2" @ 5222'
Casing Logger | 5215'
Bit Type | STC
Type Mud | GEL CHEM
Density | 9.2
Viscosity | 38
Fluid Loss | 6.4
Source of Sample | FLOWLINE
Rm @ Meas. Temp. | 1.52 @ 70°F
Rmf @ Meas. Temp. | 1.14 @ 70°F
Rmc @ Meas. Temp. | 2.28 @ 70°F
Source of Rmf / Rmc | MEASURED / CALCULATED
Rm @ BHT | 1.00 @ 120°F
Time Since Circulation | 12 HRS
Max. Rec. Temp. Deg. F | 120
Equipment Number | 5062-C
Location | GALLIA
Recorded By | D. SHEETS
Witnessed By | MR. MITCHELL

RUN NUMBER | ONE
Bit No. | 1
Bit Size | 7 7/8"
Type Bit | STC
Depth Driller | 5222
Depth Logger | 5215
Bottom Logged Interval | 5210
Top Logged Interval | 1100
Type Fluid in Hole | GEL CHEM
Salinity, PPM Cl | 1000
Density / Viscosity | 9.2 / 38
pH / Fluid Loss | 10.5 / 6.4
Source of Sample | FLOWLINE
Rm @ Meas. Temp. | 1.52 @ 70°F
Rmf @ Meas. Temp. | 1.14 @ 70°F
Rmc @ Meas. Temp. | 2.28 @ 70°F
Source of Rmf / Rmc | MEASURED / CALCULATED
Rm @ BHT | 1.00 @ 120°F
Time Since Circulation | 12 HRS
Max. Rec. Temp. Deg. F | 120
Equipment Number | 5062-C
Location | GALLIA
Recorded By | D. SHEETS
Witnessed By | MR. MITCHELL

RUN NUMBER | TWO
Bit No. | 2
Bit Size | 7 7/8"
Type Bit | STC
Depth Driller | 5222
Depth Logger | 5215
Bottom Logged Interval | 5210
Top Logged Interval | 1100
Type Fluid in Hole | GEL CHEM
Salinity, PPM Cl | 1000
Density / Viscosity | 9.2 / 38
pH / Fluid Loss | 10.5 / 6.4
Source of Sample | FLOWLINE
Rm @ Meas. Temp. | 1.52 @ 70°F
Rmf @ Meas. Temp. | 1.14 @ 70°F
Rmc @ Meas. Temp. | 2.28 @ 70°F
Source of Rmf / Rmc | MEASURED / CALCULATED
Rm @ BHT | 1.00 @ 120°F
Time Since Circulation | 12 HRS
Max. Rec. Temp. Deg. F | 120
Equipment Number | 5062-C
Location | GALLIA
Recorded By | D. SHEETS
Witnessed By | MR. MITCHELL

| | |
|---|---|
| Company | MITCHELL ENERGY CORPORATION |
| Well | TL EXETER 11-9 |
| Field | WILDCAT |
| County | GALLIA |
| State | OHIO |
| Location | 1980' FSL & 1980' FEL |
| Sec. | 9 |
| Twp. | 4 NORTH |
| Rge. | 14 WEST |
| Permanent Datum | GROUND LEVEL |
| Elev. | 668 |
| Log Measured From | KELLY BUSHING |
| Drilling Measured From | KELLY BUSHING |
| Elev. K.B. | 688 |
| Elev. D.F. | 687 |
| Elev. G.L. | 668 |

RUN NUMBER | THREE
Bit No. | 3
Bit Size | 7 7/8"
Type Bit | STC
Depth Driller | 5222
Depth Logger | 5215
Bottom Logged Interval | 5210
Top Logged Interval | 1100
Type Fluid in Hole | GEL CHEM
Salinity, PPM Cl | 1000
Density / Viscosity | 9.2 / 38
pH / Fluid Loss | 10.5 / 6.4
Source of Sample | FLOWLINE
Rm @ Meas. Temp. | 1.52 @ 70°F
Rmf @ Meas. Temp. | 1.14 @ 70°F
Rmc @ Meas. Temp. | 2.28 @ 70°F
Source of Rmf / Rmc | MEASURED / CALCULATED
Rm @ BHT | 1.00 @ 120°F
Time Since Circulation | 12 HRS
Max. Rec. Temp. Deg. F | 120
Equipment Number | 5062-C
Location | GALLIA
Recorded By | D. SHEETS
Witnessed By | MR. MITCHELL

RUN NUMBER | FOUR
Bit No. | 4
Bit Size | 7 7/8"
Type Bit | STC
Depth Driller | 5222
Depth Logger | 5215
Bottom Logged Interval | 5210
Top Logged Interval | 1100
Type Fluid in Hole | GEL CHEM
Salinity, PPM Cl | 1000
Density / Viscosity | 9.2 / 38
pH / Fluid Loss | 10.5 / 6.4
Source of Sample | FLOWLINE
Rm @ Meas. Temp. | 1.52 @ 70°F
Rmf @ Meas. Temp. | 1.14 @ 70°F
Rmc @ Meas. Temp. | 2.28 @ 70°F
Source of Rmf / Rmc | MEASURED / CALCULATED
Rm @ BHT | 1.00 @ 120°F
Time Since Circulation | 12 HRS
Max. Rec. Temp. Deg. F | 120
Equipment Number | 5062-C
Location | GALLIA
Recorded By | D. SHEETS
Witnessed By | MR. MITCHELL

| | |
|---|---|
| Company | MITCHELL ENERGY CORPORATION |
| Well | TL EXETER 11-9 |
| Field | WILDCAT |
| County | GALLIA |
| State | OHIO |
| Location | 1980' FSL & 1980' FEL |
| Sec. | 9 |
| Twp. | 4 NORTH |
| Rge. | 14 WEST |
| Permanent Datum | GROUND LEVEL |
| Elev. | 668 |
| Log Measured From | KELLY BUSHING |
| Drilling Measured From | KELLY BUSHING |
| Elev. K.B. | 688 |
| Elev. D.F. | 687 |
| Elev. G.L. | 668 |

RUN NUMBER | FIVE
Bit No. | 5
Bit Size | 7 7/8"
Type Bit | STC
Depth Driller | 5222
Depth Logger | 5215
Bottom Logged Interval | 5210
Top Logged Interval | 1100
Type Fluid in Hole | GEL CHEM
Salinity, PPM Cl | 1000
Density / Viscosity | 9.2 / 38
pH / Fluid Loss | 10.5 / 6.4
Source of Sample | FLOWLINE
Rm @ Meas. Temp. | 1.52 @ 70°F
Rmf @ Meas. Temp. | 1.14 @ 70°F
Rmc @ Meas. Temp. | 2.28 @ 70°F
Source of Rmf / Rmc | MEASURED / CALCULATED
Rm @ BHT | 1.00 @ 120°F
Time Since Circulation | 12 HRS
Max. Rec. Temp. Deg. F | 120
Equipment Number | 5062-C
Location | GALLIA
Recorded By | D. SHEETS
Witnessed By | MR. MITCHELL

| | |
|---|---|
| Company | MITCHELL ENERGY CORPORATION |
| Well | TL EXETER 11-9 |
| Field | WILDCAT |
| County | GALLIA |
| State | OHIO |
| Location | 1980' FSL & 1980' FEL |
| Sec. | 9 |
| Twp. | 4 NORTH |
| Rge. | 14 WEST |
| Permanent Datum | GROUND LEVEL |
| Elev. | 668 |
| Log Measured From | KELLY BUSHING |
| Drilling Measured From | KELLY BUSHING |
| Elev. K.B. | 688 |
| Elev. D.F. | 687 |
| Elev. G.L. | 668 |

RUN NUMBER | SIX
Bit No. | 6
Bit Size | 7 7/8"
Type Bit | STC
Depth Driller | 5222
Depth Logger | 5215
Bottom Logged Interval | 5210
Top Logged Interval | 1100
Type Fluid in Hole | GEL CHEM
Salinity, PPM Cl | 1000
Density / Viscosity | 9.2 / 38
pH / Fluid Loss | 10.5 / 6.4
Source of Sample | FLOWLINE
Rm @ Meas. Temp. | 1.52 @ 70°F
Rmf @ Meas. Temp. | 1.14 @ 70°F
Rmc @ Meas. Temp. | 2.28 @ 70°F
Source of Rmf / Rmc | MEASURED / CALCULATED
Rm @ BHT | 1.00 @ 120°F
Time Since Circulation | 12 HRS
Max. Rec. Temp. Deg. F | 120
Equipment Number | 5062-C
Location | GALLIA
Recorded By | D. SHEETS
Witnessed By | MR. MITCHELL

| | |
|---|---|
| Company | MITCHELL ENERGY CORPORATION |
| Well | TL EXETER 11-9 |
| Field | WILDCAT |
| County | GALLIA |
| State | OHIO |
| Location | 1980' FSL & 1980' FEL |
| Sec. | 9 |
| Twp. | 4 NORTH |
| Rge. | 14 WEST |
| Permanent Datum | GROUND LEVEL |
| Elev. | 668 |
| Log Measured From | KELLY BUSHING |
| Drilling Measured From | KELLY BUSHING |
| Elev. K.B. | 688 |
| Elev. D.F. | 687 |
| Elev. G.L. | 668 |

RUN NUMBER | SEVEN
Bit No. | 7
Bit Size | 7 7/8"
Type Bit | STC
Depth Driller | 5222
Depth Logger | 5215
Bottom Logged Interval | 5210
Top Logged Interval | 1100
Type Fluid in Hole | GEL CHEM
Salinity, PPM Cl | 1000
Density / Viscosity | 9.2 / 38
pH / Fluid Loss | 10.5 / 6.4
Source of Sample | FLOWLINE
Rm @ Meas. Temp. | 1.52 @ 70°F
Rmf @ Meas. Temp. | 1.14 @ 70°F
Rmc @ Meas. Temp. | 2.28 @ 70°F
Source of Rmf / Rmc | MEASURED / CALCULATED
Rm @ BHT | 1.00 @ 120°F
Time Since Circulation | 12 HRS
Max. Rec. Temp. Deg. F | 120
Equipment Number | 5062-C
Location | GALLIA
Recorded By | D. SHEETS
Witnessed By | MR. MITCHELL

| | |
|---|---|
| Company | MITCHELL ENERGY CORPORATION |
| Well | TL EXETER 11-9 |
| Field | WILDCAT |
| County | GALLIA |
| State | OHIO |
| Location | 1980' FSL & 1980' FEL |
| Sec. | 9 |
| Twp. | 4 NORTH |
| Rge. | 14 WEST |
| Permanent Datum | GROUND LEVEL |
| Elev. | 668 |
| Log Measured From | KELLY BUSHING |
| Drilling Measured From | KELLY BUSHING |
| Elev. K.B. | 688 |
| Elev. D.F. | 687 |
| Elev. G.L. | 668 |

RUN NUMBER | EIGHT
Bit No. | 8
Bit Size | 7 7/8"
Type Bit | STC
Depth Driller | 5222
Depth Logger | 5215
Bottom Logged Interval | 5210
Top Logged Interval | 1100
Type Fluid in Hole | GEL CHEM
Salinity, PPM Cl | 1000
Density / Viscosity | 9.2 / 38
pH / Fluid Loss | 10.5 / 6.4
Source of Sample | FLOWLINE
Rm @ Meas. Temp. | 1.52 @ 70°F
Rmf @ Meas. Temp. | 1.14 @ 70°F
Rmc @ Meas. Temp. | 2.28 @ 70°F
Source of Rmf / Rmc | MEASURED / CALCULATED
Rm @ BHT | 1.00 @ 120°F
Time Since Circulation | 12 HRS
Max. Rec. Temp. Deg. F | 120
Equipment Number | 5062-C
Location | GALLIA
Recorded By | D. SHEETS
Witnessed By | MR. MITCHELL

| | |
|---|---|
| Company | MITCHELL ENERGY CORPORATION |
| Well | TL EXETER 11-9 |
| Field | WILDCAT |
| County | GALLIA |
| State | OHIO |
| Location | 1980' FSL & 1980' FEL |
| Sec. | 9 |
| Twp. | 4 NORTH |
| Rge. | 14 WEST |
| Permanent Datum | GROUND LEVEL |
| Elev. | 668 |
| Log Measured From | KELLY BUSHING |
| Drilling Measured From | KELLY BUSHING |
| Elev. K.B. | 688 |
| Elev. D.F. | 687 |
| Elev. G.L. | 668 |

RUN NUMBER | NINE
Bit No. | 9
Bit Size | 7 7/8"
Type Bit | STC
Depth Driller | 5222
Depth Logger | 5215
Bottom Logged Interval | 5210
Top Logged Interval | 1100
Type Fluid in Hole | GEL CHEM
Salinity, PPM Cl | 1000
Density / Viscosity | 9.2 / 38
pH / Fluid Loss | 10.5 / 6.4
Source of Sample | FLOWLINE
Rm @ Meas. Temp. | 1.52 @ 70°F
Rmf @ Meas. Temp. | 1.14 @ 70°F
Rmc @ Meas. Temp. | 2.28 @ 70°F
Source of Rmf / Rmc | MEASURED / CALCULATED
Rm @ BHT | 1.00 @ 120°F
Time Since Circulation | 12 HRS
Max. Rec. Temp. Deg. F | 120
Equipment Number | 5062-C
Location | GALLIA
Recorded By | D. SHEETS
Witnessed By | MR. MITCHELL

| | |
|---|---|
| Company | MITCHELL ENERGY CORPORATION |
| Well | TL EXETER 11-9 |
| Field | WILDCAT |
| County | GALLIA |
| State | OHIO |
| Location | 1980' FSL & 1980' FEL |
| Sec. | 9 |
| Twp. | 4 NORTH |
| Rge. | 14 WEST |
| Permanent Datum | GROUND LEVEL |
| Elev. | 668 |
| Log Measured From | KELLY BUSHING |
| Drilling Measured From | KELLY BUSHING |
| Elev. K.B. | 688 |
| Elev. D.F. | 687 |
| Elev. G.L. | 668 |

RUN NUMBER | TEN
Bit No. | 10
Bit Size | 7 7/8"
Type Bit | STC
Depth Driller | 5222
Depth Logger | 5215
Bottom Logged Interval | 5210
Top Logged Interval | 1100
Type Fluid in Hole | GEL CHEM
Salinity, PPM Cl | 1000
Density / Viscosity | 9.2 / 38
pH / Fluid Loss | 10.5 / 6.4
Source of Sample | FLOWLINE
Rm @ Meas. Temp. | 1.52 @ 70°F
Rmf @ Meas. Temp. | 1.14 @ 70°F
Rmc @ Meas. Temp. | 2.28 @ 70°F
Source of Rmf / Rmc | MEASURED / CALCULATED
Rm @ BHT | 1.00 @ 120°F
Time Since Circulation | 12 HRS
Max. Rec. Temp. Deg. F | 120
Equipment Number | 5062-C
Location | GALLIA
Recorded By | D. SHEETS
Witnessed By | MR. MITCHELL

| | |
|---|---|
| Company | MITCHELL ENERGY CORPORATION |
| Well | TL EXETER 11-9 |
| Field | WILDCAT |
| County | GALLIA |
| State | OHIO |
| Location | 1980' FSL & 1980' FEL |
| Sec. | 9 |
| Twp. | 4 NORTH |
| Rge. | 14 WEST |
| Permanent Datum | GROUND LEVEL |
| Elev. | 668 |
| Log Measured From | KELLY BUSHING |
| Drilling Measured From | KELLY BUSHING |
| Elev. K.B. | 688 |
| Elev. D.F. | 687 |
| Elev. G.L. | 668 |

RUN NUMBER | ELEVEN
Bit No. | 11
Bit Size | 7 7/8"
Type Bit | STC
Depth Driller | 5222
Depth Logger | 5215
Bottom Logged Interval | 5210
Top Logged Interval | 1100
Type Fluid in Hole | GEL CHEM
Salinity, PPM Cl | 1000
Density / Viscosity | 9.2 / 38
pH / Fluid Loss | 10.5 / 6.4
Source of Sample | FLOWLINE
Rm @ Meas. Temp. | 1.52 @ 70°F
Rmf @ Meas. Temp. | 1.14 @ 70°F
Rmc @ Meas. Temp. | 2.28 @ 70°F
Source of Rmf / Rmc | MEASURED / CALCULATED
Rm @ BHT | 1.00 @ 120°F
Time Since Circulation | 12 HRS
Max. Rec. Temp. Deg. F | 120
Equipment Number | 5062-C
Location | GALLIA
Recorded By | D. SHEETS
Witnessed By | MR. MITCHELL

| | |
|---|---|
| Company | MITCHELL ENERGY CORPORATION |
| Well | TL EXETER 11-9 |
| Field | WILDCAT |
| County | GALLIA |
| State | OHIO |
| Location | 1980' FSL & 1980' FEL |
| Sec. | 9 |
| Twp. | 4 NORTH |
| Rge. | 14 WEST |
| Permanent Datum | GROUND LEVEL |
| Elev. | 668 |
| Log Measured From | KELLY BUSHING |
| Drilling Measured From | KELLY BUSHING |
| Elev. K.B. | 688 |
| Elev. D.F. | 687 |
| Elev. G.L. | 668 |

RUN NUMBER | TWELVE
Bit No. | 12
Bit Size | 7 7/8"
Type Bit | STC
Depth Driller | 5222
Depth Logger | 5215
Bottom Logged Interval | 5210
Top Logged Interval | 1100
Type Fluid in Hole | GEL CHEM
Salinity, PPM Cl | 1000
Density / Viscosity | 9.2 / 38
pH / Fluid Loss | 10.5 / 6.4
Source of Sample | FLOWLINE
Rm @ Meas. Temp. | 1.52 @ 70°F
Rmf @ Meas. Temp. | 1.14 @ 70°F
Rmc @ Meas. Temp. | 2.28 @ 70°F
Source of Rmf / Rmc | MEASURED / CALCULATED
Rm @ BHT | 1.00 @ 120°F
Time Since Circulation | 12 HRS
Max. Rec. Temp. Deg. F | 120
Equipment Number | 5062-C
Location | GALLIA
Recorded By | D. SHEETS
Witnessed By | MR. MITCHELL

| | |
|---|---|
| Company | MITCHELL ENERGY CORPORATION |
| Well | TL EXETER 11-9 |
| Field | WILDCAT |
| County | GALLIA |
| State | OHIO |
| Location | 1980' FSL & 1980' FEL |
| Sec. | 9 |
| Twp. | 4 NORTH |
| Rge. | 14 WEST |
| Permanent Datum | GROUND LEVEL |
| Elev. | 668 |
| Log Measured From | KELLY BUSHING |
| Drilling Measured From | KELLY BUSHING |
| Elev. K.B. | 688 |
| Elev. D.F. | 687 |
| Elev. G.L. | 668 |

RUN NUMBER | THIRTEEN
Bit No. | 13
Bit Size | 7 7/8"
Type Bit | STC
Depth Driller | 5222
Depth Logger | 5215
Bottom Logged Interval | 5210
Top Logged Interval | 1100
Type Fluid in Hole | GEL CHEM
Salinity, PPM Cl | 1000
Density / Viscosity | 9.2 / 38
pH / Fluid Loss | 10.5 / 6.4
Source of Sample | FLOWLINE
Rm @ Meas. Temp. | 1.52 @ 70°F
Rmf @ Meas. Temp. | 1.14 @ 70°F
Rmc @ Meas. Temp. | 2.28 @ 70°F
Source of Rmf / Rmc | MEASURED / CALCULATED
Rm @ BHT | 1.00 @ 120°F
Time Since Circulation | 12 HRS
Max. Rec. Temp. Deg. F | 120
Equipment Number | 5062-C
Location | GALLIA
Recorded By | D. SHEETS
Witnessed By | MR. MITCHELL

| | |
|---|---|
| Company | MITCHELL ENERGY CORPORATION |
| Well | TL EXETER 11-9 |
| Field | WILDCAT |
| County | GALLIA |
| State | OHIO |
| Location | 1980' FSL & 1980' FEL |
| Sec. | 9 |
| Twp. | 4 NORTH |
| Rge. | 14 WEST |
| Permanent Datum | GROUND LEVEL |
| Elev. | 668 |
| Log Measured From | KELLY BUSHING |
| Drilling Measured From | KELLY BUSHING |
| Elev. K.B. | 688 |
| Elev. D.F. | 687 |
| Elev. G.L. | 668 |

RUN NUMBER | FOURTEEN
Bit No. | 14
Bit Size | 7 7/8"
Type Bit | STC
Depth Driller | 5222
Depth Logger | 5215
Bottom Logged Interval | 5210
Top Logged Interval | 1100
Type Fluid in Hole | GEL CHEM
Salinity, PPM Cl | 1000
Density / Viscosity | 9.2 / 38
pH / Fluid Loss | 10.5 / 6.4
Source of Sample | FLOWLINE
Rm @ Meas. Temp. | 1.52 @ 70°F
Rmf @ Meas. Temp. | 1.14 @ 70°F
Rmc @ Meas. Temp. | 2.28 @ 70°F
Source of Rmf / Rmc | MEASURED / CALCULATED
Rm @ BHT | 1.00 @ 120°F
Time Since Circulation | 12 HRS
Max. Rec. Temp. Deg. F | 120
Equipment Number | 5062-C
Location | GALLIA
Recorded By | D. SHEETS
Witnessed By | MR. MITCHELL

| | |
|---|---|
| Company | MITCHELL ENERGY CORPORATION |
| Well | TL EXETER 11-9 |
| Field | WILDCAT |
| County | GALLIA |
| State | OHIO |
| Location | 1980' FSL & 1980' FEL |
| Sec. | 9 |
| Twp. | 4 NORTH |
| Rge. | 14 WEST |
| Permanent Datum | GROUND LEVEL |
| Elev. | 668 |
| Log Measured From | KELLY BUSHING |
| Drilling Measured From | KELLY BUSHING |
| Elev. K.B. | 688 |
| Elev. D.F. | 687 |
| Elev. G.L. | 668 |

RUN NUMBER | FIFTEEN
Bit No. | 15
Bit Size | 7 7/8"
Type Bit | STC
Depth Driller | 5222
Depth Logger | 5215
Bottom Logged Interval | 5210
Top Logged Interval | 1100
Type Fluid in Hole | GEL CHEM
Salinity, PPM Cl | 1000
Density / Viscosity | 9.2 / 38
pH / Fluid Loss | 10.5 / 6.4
Source of Sample | FLOWLINE
Rm @ Meas. Temp. | 1.52 @ 70°F
Rmf @ Meas. Temp. | 1.14 @ 70°F
Rmc @ Meas. Temp. | 2.28 @ 70°F
Source of Rmf / Rmc | MEASURED / CALCULATED
Rm @ BHT | 1.00 @ 120°F
Time Since Circulation | 12 HRS
Max. Rec. Temp. Deg. F | 120
Equipment Number | 5062-C
Location | GALLIA
Recorded By | D. SHEETS
Witnessed By | MR. MITCHELL

| | |
|---|---|
| Company | MITCHELL ENERGY CORPORATION |
| Well | TL EXETER 11-9 |
| Field | WILDCAT |
| County | GALLIA |
| State | OHIO |
| Location | 1980' FSL & 1980' FEL |
| Sec. | 9 |
| Twp. | 4 NORTH |
| Rge. | 14 WEST |
| Permanent Datum | GROUND LEVEL |
| Elev. | 668 |
| Log Measured From | KELLY BUSHING |
| Drilling Measured From | KELLY BUSHING |
| Elev. K.B. | 688 |
| Elev. D.F. | 687 |
| Elev. G.L. | 668 |

RUN NUMBER | SIXTEEN
Bit No. | 16
Bit Size | 7 7/8"
Type Bit | STC
Depth Driller | 5222
Depth Logger | 5215
Bottom Logged Interval | 5210
Top Logged Interval | 1100
Type Fluid in Hole | GEL CHEM
Salinity, PPM Cl | 1000
Density / Viscosity | 9.2 / 38
pH / Fluid Loss | 10.5 / 6.4
Source of Sample | FLOWLINE
Rm @ Meas. Temp. | 1.52 @ 70°F
Rmf @ Meas. Temp. | 1.14 @ 70°F
Rmc @ Meas. Temp. | 2.28 @ 70°F
Source of Rmf / Rmc | MEASURED / CALCULATED
Rm @ BHT | 1.00 @ 120°F
Time Since Circulation | 12 HRS
Max. Rec. Temp. Deg. F | 120
Equipment Number | 5062-C
Location | GALLIA
Recorded By | D. SHEETS
Witnessed By | MR. MITCHELL

| | |
|---|---|
| Company | MITCHELL ENERGY CORPORATION |
| Well | TL EXETER 11-9 |
| Field | WILDCAT |
| County | GALLIA |
| State | OHIO |
| Location | 1980' FSL & 1980' FEL |
| Sec. | 9 |
| Twp. | 4 NORTH |
| Rge. | 14 WEST |
| Permanent Datum | GROUND LEVEL |
| Elev. | 668 |
| Log Measured From | KELLY BUSHING |
| Drilling Measured From | KELLY BUSHING |
| Elev. K.B. | 688 |
| Elev. D.F. | 687 |
| Elev. G.L. | 668 |

RUN NUMBER | SEVENTEEN
Bit No. | 17
Bit Size | 7 7/8"
Type Bit | STC
Depth Driller | 5222
Depth Logger | 5215
Bottom Logged Interval | 5210
Top Logged Interval | 1100
Type Fluid in Hole | GEL CHEM
Salinity, PPM Cl | 1000
Density / Viscosity | 9.2 / 38
pH / Fluid Loss | 10.5 / 6.4
Source of Sample | FLOWLINE
Rm @ Meas. Temp. | 1.52 @ 70°F
Rmf @ Meas. Temp. | 1.14 @ 70°F
Rmc @ Meas. Temp. | 2.28 @ 70°F
Source of Rmf / Rmc | MEASURED / CALCULATED
Rm @ BHT | 1.00 @ 120°F
Time Since Circulation | 12 HRS
Max. Rec. Temp. Deg. F | 120
Equipment Number | 5062-C
Location | GALLIA
Recorded By | D. SHEETS
Witnessed By | MR. MITCHELL

| | |
|---|---|
| Company | MITCHELL ENERGY CORPORATION |
| Well | TL EXETER 11-9 |
| Field | WILDCAT |
| County | GALLIA |
| State | OHIO |
| Location | 1980' FSL & 1980' FEL |
| Sec. | 9 |
| Twp. | 4 NORTH |
| Rge. | 14 WEST |
| Permanent Datum | GROUND LEVEL |
| Elev. | 668 |
| Log Measured From | KELLY BUSHING |
| Drilling Measured From | KELLY BUSHING |
| Elev. K.B. | 688 |
| Elev. D.F. | 687 |
| Elev. G.L. | 668 |

RUN NUMBER | EIGHTEEN
Bit No. | 18
Bit Size | 7 7/8"
Type Bit | STC
Depth Driller | 5222
Depth Logger | 5215
Bottom Logged Interval | 5210
Top Logged Interval | 1100
Type Fluid in Hole | GEL CHEM
Salinity, PPM Cl | 1000
Density / Viscosity | 9.2 / 38
pH / Fluid Loss | 10.5 / 6.4
Source of Sample | FLOWLINE
Rm @ Meas. Temp. | 1.52 @ 70°F
Rmf @ Meas. Temp. | 1.14 @ 70°F
Rmc @ Meas. Temp. | 2.28 @ 70°F
Source of Rmf / Rmc | MEASURED / CALCULATED
Rm @ BHT | 1.00 @ 120°F
Time Since Circulation | 12 HRS
Max. Rec. Temp. Deg. F | 120
Equipment Number | 5062-C
Location | GALLIA
Recorded By | D. SHEETS
Witnessed By | MR. MITCHELL

| | |
|---|---|
| Company | MITCHELL ENERGY CORPORATION |
| Well | TL EXETER 11-9 |
| Field | WILDCAT |
| County | GALLIA |
| State | OHIO |
| Location | 1980' FSL & 1980' FEL |
| Sec. | 9 |
| Twp. | 4 NORTH |
| Rge. | 14 WEST |
| Permanent Datum | GROUND LEVEL |
| Elev. | 668 |
| Log Measured From | KELLY BUSHING |
| Drilling Measured From | KELLY BUSHING |
| Elev. K.B. | 688 |
| Elev. D.F. | 687 |
| Elev. G.L. | 668 |

RUN NUMBER | NINETEEN
Bit No. | 19
Bit Size | 7 7/8"
Type Bit | STC
Depth Driller | 5222
Depth Logger | 5215
Bottom Logged Interval | 5210
Top Logged Interval | 1100
Type Fluid in Hole | GEL CHEM
Salinity, PPM Cl | 1000
Density / Viscosity | 9.2 / 38
pH / Fluid Loss | 10.5 / 6.4
Source of Sample | FLOWLINE
Rm @ Meas. Temp. | 1.52 @ 70°F
Rmf @ Meas. Temp. | 1.14 @ 70°F
Rmc @ Meas. Temp. | 2.28 @ 70°F
Source of Rmf / Rmc | MEASURED / CALCULATED
Rm @ BHT | 1.00 @ 120°F
Time Since Circulation | 12 HRS
Max. Rec. Temp. Deg. F | 120
Equipment Number | 5062-C
Location | GALLIA
Recorded By | D. SHEETS
Witnessed By | MR. MITCHELL

| | |
|---|---|
| Company | MITCHELL ENERGY CORPORATION |
| Well | TL EXETER 11-9 |
| Field | WILDCAT |
| County | GALLIA |
| State | OHIO |
| Location | 1980' FSL & 1980' FEL |
| Sec. | 9 |
| Twp. | 4 NORTH |
| Rge. | 14 WEST |
| Permanent Datum | GROUND LEVEL |
| Elev. | 668 |
| Log Measured From | KELLY BUSHING |
| Drilling Measured From | KELLY BUSHING |
| Elev. K.B. | 688 |
| Elev. D.F. | 687 |
| Elev. G.L. | 668 |

RUN NUMBER | TWENTY
Bit No. | 20
Bit Size | 7 7/8"
Type Bit | STC
Depth Driller | 5222
Depth Logger | 5215
Bottom Logged Interval | 5210
Top Logged Interval | 1100
Type Fluid in Hole | GEL CHEM
Salinity, PPM Cl | 1000
Density / Viscosity | 9.2 / 38
pH / Fluid Loss | 10.5 / 6.4
Source of Sample | FLOWLINE
Rm @ Meas. Temp. | 1.52 @ 70°F
Rmf @ Meas. Temp. | 1.14 @ 70°F
Rmc @ Meas. Temp. | 2.28 @ 70°F
Source of Rmf / Rmc | MEASURED / CALCULATED
Rm @ BHT | 1.00 @ 120°F
Time Since Circulation | 12 HRS
Max. Rec. Temp. Deg. F | 120
Equipment Number | 5062-C
Location | GALLIA
Recorded By | D. SHEETS
Witnessed By | MR. MITCHELL

| | |
|---|---|
| Company | MITCHELL ENERGY CORPORATION |
| Well | TL EXETER 11-9 |
| Field | WILDCAT |
| County | GALLIA |
| State | OHIO |
| Location | 1980' FSL & 1980' FEL |
| Sec. | 9 |
| Twp. | 4 NORTH |
| Rge. | 14 WEST |
| Permanent Datum | GROUND LEVEL |
| Elev. | 668 |
| Log Measured From | KELLY BUSHING |
| Drilling Measured From | KELLY BUSHING |
| Elev. K.B. | 688 |
| Elev. D.F. | 687 |
| Elev. G.L. | 668 |

RUN NUMBER | TWENTY-ONE
Bit No. | 21
Bit Size | 7 7/8"
Type Bit | STC
Depth Driller | 5222
Depth Logger | 5215
Bottom Logged Interval | 5210
Top Logged Interval | 1100
Type Fluid in Hole | GEL CHEM
Salinity, PPM Cl | 1000
Density / Viscosity | 9.2 / 38
pH / Fluid Loss | 10.5 / 6.4
Source of Sample | FLOWLINE
Rm @ Meas. Temp. | 1.52 @ 70°F
Rmf @ Meas. Temp. | 1.14 @ 70°F
Rmc @ Meas. Temp. | 2.28 @ 70°F
Source of Rmf / Rmc | MEASURED / CALCULATED
Rm @ BHT | 1.00 @ 120°F
Time Since Circulation | 12 HRS
Max. Rec. Temp. Deg. F | 120
Equipment Number | 5062-C
Location | GALLIA
Recorded By | D. SHEETS
Witnessed By | MR. MITCHELL

| | |
|---|---|
| Company | MITCHELL ENERGY CORPORATION |
| Well | TL EXETER 11-9 |
| Field | WILDCAT |
| County | GALLIA |
| State | OHIO |
| Location | 1980' FSL & 1980' FEL |
| Sec. | 9 |
| Twp. | 4 NORTH |
| Rge. | 14 WEST |
| Permanent Datum | GROUND LEVEL |
| Elev. | 668 |
| Log Measured From | KELLY BUSHING |
| Drilling Measured From | KELLY BUSHING |
| Elev. K.B. | 688 |
| Elev. D.F. | 687 |
| Elev. G.L. | 668 |

RUN NUMBER | TWENTY-TWO
Bit No. | 22
Bit Size | 7 7/8"
Type Bit | STC
Depth Driller | 5222
Depth Logger | 5215
Bottom Logged Interval | 5210
Top Logged Interval | 1100
Type Fluid in Hole | GEL CHEM
Salinity, PPM Cl | 1000
Density / Viscosity | 9.2 / 38
pH / Fluid Loss | 10.5 / 6.4
Source of Sample | FLOWLINE
Rm @ Meas. Temp. | 1.52 @ 70°F
Rmf @ Meas. Temp. | 1.14 @ 70°F
Rmc @ Meas. Temp. | 2.28 @ 70°F
Source of Rmf / Rmc | MEASURED / CALCULATED
Rm @ BHT | 1.00 @ 120°F
Time Since Circulation | 12 HRS
Max. Rec. Temp. Deg. F | 120
Equipment Number | 5062-C
Location | GALLIA
Recorded By | D. SHEETS
Witnessed By | MR. MITCHELL

| | |
|---|---|
| Company | MITCHELL ENERGY CORPORATION |
| Well | TL EXETER 11-9 |
| Field | WILDCAT |
| County | GALLIA |
| State | OHIO |
| Location | 1980' FSL & 1980' FEL |
| Sec. | 9 |
| Twp. | 4 NORTH |
| Rge. | 14 WEST |
| Permanent Datum | GROUND LEVEL |
| Elev. | 668 |
| Log Measured From | KELLY BUSHING |
| Drilling Measured From | KELLY BUSHING |
| Elev. K.B. | 688 |
| Elev. D.F. | 687 |
| Elev. G.L. | 668 |

RUN NUMBER | TWENTY-THREE
Bit No. | 23
Bit Size | 7 7/8"
Type Bit | STC
Depth Driller | 5222
Depth Logger | 5215
Bottom Logged Interval | 5210
Top Logged Interval | 1100
Type Fluid in Hole | GEL CHEM
Salinity, PPM Cl | 1000
Density / Viscosity | 9.2 / 38
pH / Fluid Loss | 10.5 / 6.4
Source of Sample | FLOWLINE
Rm @ Meas. Temp. | 1.52 @ 70°F
Rmf @ Meas. Temp. | 1.14 @ 70°F
Rmc @ Meas. Temp. | 2.28 @ 70°F
Source of Rmf / Rmc | MEASURED / CALCULATED
Rm @ BHT | 1.00 @ 120°F
Time Since Circulation | 12 HRS
Max. Rec. Temp. Deg. F | 120
Equipment Number | 5062-C
Location | GALLIA
Recorded By | D. SHEETS
Witnessed By | MR. MITCHELL

| | |
|---|---|
| Company | MITCHELL ENERGY CORPORATION |
| Well | TL EXETER 11-9 |
| Field | WILDCAT |
| County | GALLIA |
| State | OHIO |
| Location | 1980' FSL & 1980' FEL |
| Sec. | 9 |
| Twp. | 4 NORTH |
| Rge. | 14 WEST |
| Permanent Datum | GROUND LEVEL |
| Elev. | 668 |
| Log Measured From | KELLY BUSHING |
| Drilling Measured From | KELLY BUSHING |
| Elev. K.B. | 688 |
| Elev. D.F. | 687 |
| Elev. G.L. | 668 |

RUN NUMBER | TWENTY-FOUR
Bit No. | 24
Bit Size | 7 7/8"
Type Bit | STC
Depth Driller | 5222
Depth Logger | 5215
Bottom Logged Interval | 5210
Top Logged Interval | 1100
Type Fluid in Hole | GEL CHEM
Salinity, PPM Cl | 1000
Density / Viscosity | 9.2 / 38
pH / Fluid Loss | 10.5 / 6.4
Source of Sample | FLOWLINE
Rm @ Meas. Temp. | 1.52 @ 70°F
Rmf @ Meas. Temp. | 1.14 @ 70°F
Rmc @ Meas. Temp. | 2.28 @ 70°F
Source of Rmf / Rmc | ME


REPEAT SECTION
LITHODENSITY REPEAT SECTION
GAMMA RAY API UNITS
CALIPER INCHES OR METERS
INTEGRATED TRANSIT TIME
INTERVAL TRANSIT TIME
MICROSECONDS PER FOOT
CALIBRATION RECORD
CALIBRATION AFTER SURVEY
CALIBRATION BEFORE SURVEY
CALIBRATION RECORD
COMPANY PETROLEUM ENERGY CORPORATION
WELL EL GRANDE 11-9
FIELD WILDCAT
COUNTY SAN JUAN
STATE UTAH
SONIC No. 1252
DENSITY No. 1252
DATA No. 1252
Run No. ONE
Date 5-28