



## Current CO<sub>2</sub> EOR Operations

Currently, over 48 million metric tons (tonnes) per year of CO<sub>2</sub> are used for EOR. Of this total, about 25 percent (12 million tonnes) is anthropogenic in origin i.e., produced by human activities such as oil refining or fertilizer manufacturing (Trinity 2006). The rest is extracted from naturally occurring deposits.

The CO<sub>2</sub> used to increase oil production is an expensive commodity, and for this reason oil companies are motivated to ensure that up to three quarters of CO<sub>2</sub> injected remains underground in the oil field. The amount of CO<sub>2</sub> sequestered is highly dependent on whether the field is blown-down following any CO<sub>2</sub> operations. Further research and development in this area is expected to improve the storage rate to close to 100 percent. Estimates made by the U.S. Department of Energy (DOE) show that depleted oil and gas wells in the United States and Canada have the potential to sequester over 82 billion tonnes of carbon in total (DOE 2007).

Table 1. CO<sub>2</sub> Utilization and Potential in EOR Projects

United States (2006)	(million tonnes/yr)
Carbon Dioxide use for EOR	48
• Naturally occurring	36
• Anthropogenic	12
Estimated CO <sub>2</sub> sequestered by EOR operations	9
<b>Worldwide</b>	
Potential CO <sub>2</sub> EOR sequestration	130 billion tonnes
<b>Total CO<sub>2</sub> accumulated in atmosphere</b>	<b>3-4 billion tonnes/yr</b>

Source of U.S. data: National Energy Technology Laboratory, Carbon Sequestration Atlas, 2007

## Benefits

CO<sub>2</sub> EOR is a promising method of sequestration for a number of reasons. First, the geologic structures that originally contained the oil and natural gas should also permanently contain the injected CO<sub>2</sub>, provided the integrity of the structures is maintained. From seismic studies, the geologic structure and physical properties of many oil and gas fields are well understood. This, combined with the vast amount of industry experience with gas-injection EOR, provides a knowledge base from which to start researching the sequestration implications of CO<sub>2</sub> EOR. Another benefit of CO<sub>2</sub> EOR for sequestration purposes is the widespread distribution of depleted and operating oil and gas fields, making it likely that an oil field is near a CO<sub>2</sub> source. Finally, carbon sequestration from CO<sub>2</sub> EOR projects can create offsets resulting in trades in the emerging greenhouse gas market. CO<sub>2</sub>e.com has conducted a transaction between Ontario Power Generation and Bluesource. The forward purchase of 6 million tonnes of CO<sub>2</sub> equivalent and option for an additional 3 million tonnes of CO<sub>2</sub> equivalent resulted from geologic sequestration projects in Texas, Wyoming, and Mississippi, where CO<sub>2</sub> that would otherwise be vented by natural gas processing plants is used for enhanced oil recovery.

## Industries Activities

CO<sub>2</sub> is specifically processed for most of the 82 projects utilizing CO<sub>2</sub> for EOR (Moritis, 2006). The CO<sub>2</sub> for these projects is mined from naturally occurring, high-pressure deposits that occur close enough to oil fields to make transmission economically feasible. The following table lists DOE-sponsored projects that utilize anthropogenic CO<sub>2</sub> for EOR and additionally promote GHG reduction, since this CO<sub>2</sub> would otherwise be vented to the atmosphere.

Table 1. Examples of DOE- Sponsored CO<sub>2</sub> Sequestration Projects in the U.S. Involving EOR

EOR Field	CO <sub>2</sub> Source	Geological Stratum	Injection Start Date	Cumulative CO <sub>2</sub> Injection	Description
Zama Field, Alberta, Canada	Natural Gas Processing Plant	Pinnacle Reef, Middle Devonian Keg River	December 2006	230,000 tons	The Zama oil field validation test being conducted in Alberta, Canada, is evaluating the potential for geologic sequestration of CO <sub>2</sub> in an acid gas stream that also includes high concentrations of hydrogen sulfide (H <sub>2</sub> S) for the concurrent purposes of CO <sub>2</sub> sequestration, H <sub>2</sub> S disposal, and EOR. The acid gas is generated as a by-product during the processing of raw natural gas being extracted from the field.
Williston Basin	Pulverized Coal Power Plant	Devonian Duperow or Mississippian Madison Group	2011	500,000 tons/year	The Williston Basin demonstration test will evaluate the potential for geological sequestration of CO <sub>2</sub> in a deep carbonate reservoir for the dual purpose of CO <sub>2</sub> sequestration and EOR. Characterization studies indicate that the oil fields of the Williston Basin may have over 1 billion tons of CO <sub>2</sub> storage capacity. Additionally, the volume of incremental oil that could be produced from Williston Basin oil fields has been estimated to be approximately 1 billion barrels.
Louden Field, Illinois	Refinery or Ethanol Plant	Mississippian Weiler Sandstone	March 2007	43 tons	The Louden field test, an enhanced oil recovery "huff-n-puff" project, is designed to inject (huff) CO <sub>2</sub> into a producing well for 3-5 days, allow the gas to soak for approximately one week, then place the well back on production and measure the amount of petroleum fluids produced (puff).
Louden Field, Illinois	Refinery or Ethanol Plant	Mississippian Weiler Sandstone	February 2008	2,500 tons	The well conversion EOR field test does not require the drilling of any new wells because available well(s) will be converted to handle CO <sub>2</sub> injection and the pattern and spacing of existing wells is adequate to test EOR processes in the reservoir. Well conversion represents a potential near-term, low-cost opportunity to implement EOR.
Snyder, Permian Basin, Texas	McElmo Dome	Strawn- and Canyon-age carbonate reefs	Second Quarter 2008	700,000 tons	This test will include a post-audit modeling analysis of injected CO <sub>2</sub> for EOR over the last 30 years at the SACROC Unit in the Permian Basin of Texas, in addition to intense monitoring analyses of ongoing CO <sub>2</sub> injection at SACROC.
Aneth Oil Field, Bluff, Utah	McElmo Dome	Paradox Formation, Pennsylvanian Desert Creek	Second Quarter 2007	300,000 tons	The primary research objective of this EOR-sequestration test is to evaluate and maximize the efficacy of CO <sub>2</sub> subsurface monitoring technologies, and to improve the ability to track the fate of injected CO <sub>2</sub> and to calculate ultimate storage capacity.
Weyburn, Saskatchewan	Dakota Gasification Plant	The Midale Beds of the Mississippian Charles Formation,	September 2000	33 million tons	The Weyburn program is organized around five technical themes: geological integrity, wellbore integrity, storage monitoring methods, risk assessment and storage mechanisms, and data validation and management. The technical objectives are to determine the long-term storage risks and monitoring requirements to mitigate such risks.

Source: National Energy Technology Laboratory

## ADDRESS

### National Energy Technology Laboratory

1450 Queen Avenue SW  
Albany, OR 97321-2198  
541-967-5892

2175 University Avenue South  
Suite 201  
Fairbanks, AK 99709  
907-452-2559

3610 Collins Ferry Road  
P.O. Box 880  
Morgantown, WV 26507-0880  
304-285-4764

626 Cochran Mill Road  
P.O. Box 10940  
Pittsburgh, PA 15236-0940  
412-386-4687

One West Third Street,  
Suite 1400  
Tulsa, OK 74103-3519  
918-699-2000

## CUSTOMER SERVICE

1-800-553-7681

## WEBSITE

[www.netl.doe.gov](http://www.netl.doe.gov)

## Conclusions

CO<sub>2</sub> EOR is a promising technology to safely store CO<sub>2</sub> underground so that it cannot contribute to climate change. While this technology has been implemented by the oil industry since 1972, further research is needed to ensure that the stored CO<sub>2</sub> remains isolated from the atmosphere and the biosphere on the order of thousands of years and that the storage process remains as safe and economically viable as possible.

DOE's Carbon Sequestration Program is currently addressing the following challenges:

- Improving understanding of oil reservoir characteristics relative to CO<sub>2</sub> fate and transport
- Reducing the costs of capturing, processing, and transporting anthropogenic CO<sub>2</sub>, particularly from power generation facilities
- Further developing technologies to monitor and verify CO<sub>2</sub> storage, and
- Developing CO<sub>2</sub> emissions trading protocols.

For more information about how the research program is specifically addressing CO<sub>2</sub> EOR, visit the National Energy Technology Laboratory's Carbon Sequestration Reference Shelf at [http://www.netl.doe.gov/technologies/carbon\\_seq/refshelf/refshelf.html](http://www.netl.doe.gov/technologies/carbon_seq/refshelf/refshelf.html).

## Bibliography

1. Moritis, Guntis. 2006. "CO<sub>2</sub> Injection Gains Momentum." Oil and Gas Journal, v. 104, no. 15
2. Trinity CO<sub>2</sub>, December 2006 presentation and March 2008 phone conversation
3. U.S. Department of Energy, March 2007. Carbon Sequestration ATLAS of the United States and Canada
4. Advanced Resources International, CO<sub>2</sub>-EOR: An Enabling Bridge for The Oil Transition, American Energy Security Summit, April 2007