



### CONTACTS

**James T.Yeh**

Project Leader

National Energy Technology  
Laboratory

626 Cochran's Mill Road  
P.O. Box 10940  
Pittsburgh, PA 15236  
412-386-5737

james.yeh@netl.doe.gov

**George A. Richards**

Focus Area Leader

National Energy Technology  
Laboratory

3610 Collins Ferry Road  
P.O. Box 880  
Morgantown, WV 26507  
304-285-4458

george.richards@netl.doe.gov

**Sean I. Plasynski**

Sequestration Technology Manager

National Energy Technology  
Laboratory

626 Cochran's Mill Road  
P.O. Box 10940  
Pittsburgh, PA 15236

412-386-4867


sean.plasynski@netl.doe.gov

## AMMONIA-BASED PROCESS FOR MULTICOMPONENT REMOVAL FROM FLUE GAS

### Background

Carbon sequestration is considered a viable method of reducing carbon dioxide (CO<sub>2</sub>) emissions from large point sources. One point source, the pulverized coal-fired power generator, has been and will be in the near future the predominant power-generating technique. In response, NETL is developing an ammonia-based wet scrubbing process for capturing CO<sub>2</sub> in flue gas.

The project began as part of an international collaboration with China with an interest in the formation of ammonium bicarbonate fertilizer. However, as there is not a significant market for this type of fertilizer in the United States, NETL recognized the need to turn the ammonium bicarbonate into a regenerable CO<sub>2</sub> solvent. In an effort to control multiple acidic gases (e.g., CO<sub>2</sub>, SO<sub>2</sub>, NO<sub>x</sub>, HCl) plus fine particulates from flue gas produced by coal-burning power plants, NETL proposed the use of an ammonia-based process that is regenerative in terms of CO<sub>2</sub> capture for carbon sequestration. While the ammonium solution is used to produce ammonium sulfate and ammonium nitrate byproducts for fertilizer production, the ammonium bicarbonate byproduct is heated to release high-purity CO<sub>2</sub>, which will be sequestered. The second regeneration byproduct, ammonium carbonate solution, is recycled in the process and reused to absorb more CO<sub>2</sub>. The regenerative CO<sub>2</sub> capture chemistry is described by reversible chemistry between the ammonium carbonate and ammonium bicarbonate in an aqueous solution:



Although commercial ammonia-based processes exist for the removal of SO<sub>2</sub> and NO<sub>x</sub> from flue gas, NETL developed this additional scrubbing capability for CO<sub>2</sub> capture.



Continuous flow system for testing the ammonia-based process.

### Primary Project Goal

The primary goal is to select a regenerable CO<sub>2</sub> carrier with higher CO<sub>2</sub> carrying capacity than the only available industrial process for CO<sub>2</sub> capture—the MEA process. The process must be energy efficient, and the new robust carrier must not be degraded by O<sub>2</sub> or SO<sub>2</sub>, NO<sub>x</sub>, and other acidic gases that exist in the fossil fuel combustion flue gases.



## PARTNERS

Powerspan Corp.  
University of Pittsburgh  
Duquesne University

## ADDRESS

### National Energy Technology Laboratory

1450 Queen Avenue SW  
Albany, OR 97321-2198  
541-967-5892

2175 University Avenue South  
Suite 201  
Fairbanks, AK 99709  
907-452-2559

3610 Collins Ferry Road  
P.O. Box 880  
Morgantown, WV 26507-0880  
304-285-4764

626 Cochran's Mill Road  
P.O. Box 10940  
Pittsburgh, PA 15236-0940  
412-386-4687

One West Third Street, Suite 1400  
Tulsa, OK 74103-3519  
918-699-2000

## CUSTOMER SERVICE

1-800-553-7681

## WEBSITE

[www.netl.doe.gov](http://www.netl.doe.gov)



Powerspan's demonstration plant in Shadyside, OH, already cleans coal combustion flue gas to remove mercury vapor, SO<sub>2</sub>, and NO<sub>x</sub> and is expected to remove CO<sub>2</sub> as well.

## Objectives

Major objectives are to:

- Search for a carrier that has overall lower parasitic power loss than other carriers.
- Develop a process to clean criteria pollutants—including CO<sub>2</sub>—from flue gas and generate salable byproducts, such as fertilizers, that could offset the costs of terrestrial sequestration.
- Develop a single-solvent process for multicomponent control of flue gas emissions.
- Ensure the process is technically and economically feasible through a systems analysis.
- Collaborate via a CRADA with an industrial partner, Powerspan Corp., utilizing their experience with ammonia scrubbing to further develop the process.
- In partnership with the University of Pittsburgh, develop a process simulation model to aid in process scale-up to commercial size.

## Accomplishments

A continuous flow closed-loop reactor was designed and constructed, and parametric tests were performed. The effects of process operating parameters on CO<sub>2</sub> removal efficiencies were analyzed and reported. These quantification/optimization tests established major impacts of these parameters on CO<sub>2</sub> carrying capacity, ammonia losses, and ammonium species. Major ammonium species in the reactor were identified, and it was determined that excessively high temperatures during regeneration should be avoided to reduce ammonia gas loss.

## Benefits

Because of the widespread use of coal to produce power, an alternative scrubbing technique is needed to further capture CO<sub>2</sub> in flue gas. Ammonia-based scrubbing can produce technical and economic benefits compared to current scrubbing technologies. From the experimental information to date, lower parasitic energy consumption, the production of a salable fertilizer, and the capability of one solvent to remove many components are just some of the reasons that the ammonia-based process will be a significant technology in the carbon sequestration area.

