



Bench-Scale Development & Testing of a Novel Adsorption Process for Post-Combustion CO₂ Capture

DOE Funding Award DE-FE-007948

NETL CO₂ Capture Meeting

July 29, 2014

Ravi Jain

ravi.jain@innosepra.com

InnoSeptra, LLC

Middlesex, NJ

Executive Summary

- Physical sorption based process
 - Materials with low heat of sorption, $\Delta H_{\text{ads}} < 200$ Kcal/kg
 - Dry CO₂ at high purity (>98%) and high recovery (>90%)
 - Extensively tested in the lab and in the field (one ton per day scale) for period of over 6 years; little loss in performance over time
 - Product CO₂ with less than 1 pm SO_x and H₂O
- Significantly lower cost compared to MEA based on detailed internal and external evaluations
 - >45% reduction in capital
 - >40% reduction in parasitic power
 - Potential to provide CO₂ at a cost (~\$40/ton) and quality (<1 ppm H₂O, 1 ppm SO₂, <10 ppm O₂) suitable for EOR applications

Executive Summary

- The DOE Project Goals
 - Demonstrate process at one ton per day scale with real flue gas
 - Address the process risks
 - Address the effect of contaminants
 - Confirm process economics
- The DOE project outcomes
 - Various process risks and scale up issues addressed through lab and field testing, process simulation, and detailed techno-economic evaluation
 - Successful field testing with real flue gas at one ton per day scale at NRG, Indian River
 - Field performance better than the lab performance
 - **CO₂ suitable for EOR (cost and quality) can be produced**

The DOE Project Overview

Project Budget

Source	BP1 10/1/11- 12/31/12	BP2 1/1/13- 10/31/13	BP3 11/1/13- 10/30/14	Total
Dept of Energy	\$843,787	\$937,110	\$748,988	\$2,529,885
Cost Share	\$217,560	\$226,985	\$210,810	\$655,355
Total Project	\$1,061,347	\$1,164,095	\$959,798	\$3,185,240

Project Participants

DOE/NETL

- Elaine Everitt (Project Manager), Lynn Brickett, Angela Harshman, Mike Matuszewski, Shailesh Vora, James Black, and David Lang

InnoSeptra

- Technology development at lab and pilot scale leading to commercial adoption (more than 25 technologies in more than 100 plants)

EPRI

- Process modeling, economic assessment and cost share

NRG

- Field testing, commercial feedback and cost share

New Mexico State University

- Fundamental adsorption data

PNNL

- Environmental, Health & Safety (EH&S) assessment

Adsorptech

- Mechanical and controls system design, commissioning

DOE Project Objectives

Demonstrate the effectiveness of the InnoSeptra sorbent-based post-combustion CO₂ capture technology in achieving at least 90% CO₂ removal with a potential for less than a 35% increase in cost of electricity (*also <\$40/ton in the CO₂ capture cost*) as a retrofit to coal fired utility plants

- Based on lab testing and bench scale testing at NRG, Indian River plant at about one ton per day scale

and

- Scale up modeling, process and equipment design, engineering, and costing for a commercial 550 MW power plant to estimate LCOE (Levelized Cost of Electricity) and the CO₂ capture cost

Background Information

Sorption-Based CO₂ Capture


- *Capture CO₂ by physical sorption*
 - 140-240 kcal/kg (26-44 kJ/mol) heats of adsorption
 - Significantly lower than the total energy (heat of reaction + sensible heat + latent heat) for amine systems
- *Capture CO₂ by chemical reaction* with amine or carbonate based sorbents
 - 740-940 kcal/kg (136-174 kJ/mol) heats of reaction
 - Similar to the aqueous amine-based absorption systems
 - Ex. $\text{Na}_2\text{CO}_3 + \text{CO}_2 + \text{H}_2\text{O} \text{-----} > 2 \text{NaHCO}_3$
 $\Delta H_{\text{rxn}} = -740 \text{ Kcal/kg} (-136 \text{ kJ/mol})$ of CO₂
 - Possible degradation due to SO_x, NO_x, and O₂
 - May not result in energy savings compared to MEA

Effect of Adsorption Capacity on Regeneration Energy

	Carbonaceous adsorbent	Sodium carbonate adsorbent	Hypothetical Physical adsorbent
Net CO₂ Capacity, wt%	1.5	2.5	7.0
Adsorbent Density, lbs/ft ³	30	50	40
Heat of Adsorption, kcal/kg CO ₂	160	740	200
Adsorbent Sensible Heat, kcal/kg CO ₂	700	420	150
Total Heat Required Excluding Vessel Heating, kcal/kg CO ₂	860	1160	350

- Both high net CO₂ capacity and low heat of adsorption are needed to minimize the parasitic power

InnoSeptra CO₂ Capture Process



- Flue gas pretreatment to remove moisture and SO_x to <1 ppm each, adsorption at 25-40°C and regeneration at about 100°C
- High purity CO₂ (>98% CO₂, <30 ppm O₂) at >90% recovery
- Key innovation is **the combination** of process and materials (physical sorbents) that provides performance similar to or better than reactive systems and a total regeneration energy requirement of less than 450 Kcal/Kg of CO₂
- The key scale up challenges are likely to be engineering based

The DOE Project Status

Project Scope

Budget Period I – Lab Testing & Design

- Lab scale process data, adsorption/desorption isotherms and heat and mass transfer rate measurements
- Identification of the adsorbents for the removal of contaminants
- Development of a rigorous process model
- Preliminary technical and economic feasibility study
- Preliminary design & costing of the bench scale unit

Go/No-Go Decision point

Budget Period II – Procurement and Construction

- Bench unit process and mechanical design and construction (~one tpd CO₂)
- Mechanical testing of the bench scale unit

Go/No-Go Decision point

Budget Period III – Installation, Testing and Evaluation

- Installation and testing at the NRG, Indian River coal fired power plant
- Final techno-economic assessment
- Preliminary technology EH&S risk assessment




Project Overview: Key Milestones

1. Identify two adsorbent materials based on CO₂ recovery and capacity ✓
2. Obtain heat and mass transfer data ✓
3. Obtain estimate of adsorbents for moisture and contaminants ✓
4. Obtain adsorption and desorption isotherms for the preferred adsorbents ✓
5. Develop a rigorous process model ✓
6. Preliminary Technical and Economic Feasibility Study ✓
7. Detailed engineering and mechanical design of the bench scale process unit ✓
8. Fabricate the bench scale test unit ✓
9. Commission the bench-scale unit ✓
10. Bench-scale testing with flue gas from NRG's Indian River Plant
11. Final Technical and Economic Feasibility study

CO₂ Capture Testing Summary (Lab)

- More than 10 commercial and laboratory materials tested for over 5 years, >10,000 complete cycles
- Isotherm CO₂ capacities of 18-20 wt% for the flue gas from a PC plant, and a cyclic CO₂ capacities of 7-9 wt% for the preferred materials
- Regeneration temperatures of about 100°C are sufficient
- 90% CO₂ recovery and over 99% purity under optimized conditions for multi-bed experiments simulating a coal-fired power plant (13-15% CO₂)
- Less than 1 ppm each of H₂O, NO and SO_x and 10-30 ppm oxygen in the CO₂ product

Summary of Adsorbent Tests (Lab)



- For a CO₂ purity of >99% and a CO₂ recovery of >90%, net CO₂ capacities of 7-9 wt% have been obtained (~15% feed CO₂)
- Same or higher CO₂ purity, recovery and loading compared to reactive absorbents / adsorbents using materials with much weaker affinity for CO₂. Cycle modifications allow production of CO₂ with 10-30 ppm O₂.

Heat and Mass Transfer Data, Contaminants Removal

- Heat and mass transfer data obtained for various process configurations and for various process steps
- The heat transfer rates during the adsorption and regeneration steps are adequate for our process conditions and cycle times
- Moisture and SO_x removed to a level of <1 ppm each for feeds containing 50-1,000 ppm SO_x
 - Possible to handle flue gas from a non-FGD plant
- The equipment size and energy required for moisture and SO_2 removal is much smaller than that for CO_2 adsorption
 - Small impact of SO_2 and moisture removal on LCOE and the CO_2 capture cost


Process Simulation Models

- Rigorous solution of coupled heat and mass transfer partial differential equations with both the in-house simulator and ASPEN Adsorption (InnoSeptra). InnoSeptra adsorption unit integration with the power plant (EPRI).
- Single component adsorption isotherms and diffusivities from New Mexico State Data
 - Langmuir mixing rules to obtain the multicomponent isotherms from single component isotherms
- Lumped parameter model for mass transfer
 - Micropore, macropore and film diffusion resistances are combined
- The simulation is continued until a cyclic steady state is obtained
 - The simulation is computationally intensive, typically requiring more than three days for attainment of cyclic steady state
- The model has been validated with laboratory data and is being updated with data from the bench tests to improve the predictions
- EPRI modeling has provided optimum integration points for integrating the adsorption unit with the power plant

Field Demonstration of the Bench Unit

- The bench unit testing at NRG's Indian River, DE plant
 - Flue gas from unit 4 at Indian River
 - Nominal 500 MW capacity
 - SCR for NO_x control, dry FGD with recycle for SO_x control
- The bench unit takes flue gas after the dry FGD
 - The feed to bench unit is saturated at 60°C
 - About 50 ppm SO_2 , 10-12% CO_2
- The bench unit was installed and commissioned with significant help from NRG
- Testing started in May

Bench Scale Unit Skid Layout



Adsorption Skid



Cooling Tower




Heating and Cooling Skid



Field Demonstration of the Bench Unit

- Process conditions for testing
 - Two different flue gas flow rates (80 & 100 scfm)
 - 22-32°C feed temperature
 - Three different cycles for each flow rate and temperature
- About six weeks of testing has been done so far
 - Significant interruptions due to the NRG plant
- Field performance is better than the performance in the lab
 - 8-10.5 wt% net CO₂ capacity in the field
 - CO₂ recovery over 94% for product CO₂ purities between 98.5 and 99.5%
- Testing to be completed in August

Summary of Adsorbent Tests (Lab & Field)



- Significantly higher CO₂ recovery in the field compared to lab experiments

Techno-economic Analysis

The Parasitic Power

- Heat and electrical energy for the adsorption system
- Electric power for the blower, various pumps and the CO₂ compressor

The Capital Cost

- Heating and cooling system cost including direct contact cooler, pumps, blowers, and heat exchangers
- Adsorption system cost including adsorption vessels, switching valves, pumps and heat exchangers, electrical, controls, adsorbents, piping skids, shipping, engineering and installation
- CO₂ compression system cost including CO₂ compressor and interstage coolers

Energy Requirements for the Adsorption System

- Consists of
 - Pressure drop through the system
 - Heat of desorption for CO₂
 - Vessel and sieve heating
 - Sensible heat for heating CO₂ to the regeneration temperature
 - Energy required for flue gas and/or CO₂ product dehydration
 - Mechanical energy for CO₂ from the sorption system
- The total energy requirement for the InnoSeptra process, excluding compression, is <450 Kcal/Kg of CO₂


Updated Techno-economic Analysis for a 550 MW Supercritical PC Power Plant

Estimated Capital Cost	\$260 MM
Power consumption including compression (PP)	92 MW
Steam cost per 1,000 lb for the base plant	\$5.83
Steam cost with capture* = $0.028^* \text{ PP (MWe)} + 5.83$	\$8.41 (+44%)
Electricity cost for the base plant	\$0.064/kWh
Electricity cost with capture* = $0.3073^* \text{ PP (MWe)} + 64$	\$0.092/kWh (+44%)
CO ₂ production rate, million tons/yr	3.5
CO₂ Recovery Cost**	\$40.5/ton

*Based on the DE-FOA-0000403 guidelines. No explicit dependence of steam cost and LCOE on capital.

**85% plant utilization factor. Includes capital charge, maintenance, CO₂ transportation cost, and parasitic power. No increase in LCOE if CO₂ can be sold for this price.

Comparison with MEA for DOE Baseline Study



“Cost and Performance Baseline for Fossil Energy Plants”, DOE/ NETL-2007/1281, Aug 2007.
(http://www.netl.doe.gov/energyanalyses/pubs/Bituminous%20Baseline_Final%20Report.pdf)

Overall Accomplishments

- The InnoSeptra CO₂ capture process combines several innovative features to reduce the capital cost and parasitic power for CO₂ capture
- It is possible to obtain very high recovery (>90%), and high purity (>99%) CO₂ with physical sorbents while meeting the EOR/sequestration oxygen specification
 - $\Delta H_{\text{ads}} < 200$ Kcal/kg, parasitic power <450 Kcal/kg
 - High net CO₂ capacity (>8 wt%)
- The capital cost and parasitic power estimates based on a detailed component level analysis indicate that we are close to DOE's LCOE target (<35% increase) and the CO₂ cost target (<\$40/ton)
- Successful field testing at the one ton per day scale has further validated the technology

Future Plans

Current DOE Project

- Finish testing at NRG's Indian River plant
- Set commercial unit process configuration
- Independent techno-economic analysis (EPRI)
- Prepare EH&S risk assessment (PNNL)

Next Scale Up Phase

- Testing at 1.0-2.0 MW scale, also address engineering challenges related to scale up
- Results from this scale up testing can be used to design CO₂ capture systems of up to 2,000 tpd size
- Pursuing other applications that can provide technology validation in commercial applications

Summary

The major milestones for the DOE project include:

- Preferred physical sorbents for CO₂ capture identified
- Adsorption and regeneration heat transfer data obtained
- Removal of moisture and SO₂ to below 1 ppm has been experimentally verified
- Adsorption isotherms for two preferred adsorbents obtained
- The process modeled with the Process Simulator
- The bench scale unit constructed, commissioned, and tested at the one ton per day scale
- A techno-economic analysis based on the lab and field data, process simulation and detailed engineering design indicates the potential for a CO₂ capture cost below \$40/ton
 - Very attractive for EOR applications even in the absence of climate legislation
- The potential approaches to further decrease the CO₂ capture cost identified

Acknowledge and Disclaimer

Acknowledgement: The work in this presentation is supported by the Department of Energy under Award Number DE-FE0007948.

Disclaimer: "This presentation was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof."