

Pilot-Scale Silicone Process for Low-Cost CO₂ Capture

GE Global Research



GE Global
Research

Benjamin Wood




DOE Award: DE-FE0013755


2015 NETL CO₂ Capture
Technology Meeting
June 24, 2015

Overview

Program Team

 **GE Global Research**

- Pilot-scale design
- Construction/Operation of Continuous System
- EH&S Assessment
- Techno-economic Assessment
- Plant Modeling


 **National Carbon Capture Center**


- Pilot-scale Operation
- Assessment of Data
- Integration of Components




24 Month, \$5.7MM Program to Advance the Amino-Silicone Solvent Process for CO₂ Capture to Pilot Scale

Program Objectives: Design and optimize a new process for a novel silicone CO₂ capture solvent and establish scalability and potential for commercialization of post-combustion capture of CO₂ from coal-fired power plants. A primary outcome will be a system capable of 90% capture efficiency with less than \$40/tonne CO₂ capture cost.

 **Design & Optimize Process**

 **Establish Scalability & Commercial Value**

 **Pilot of Post-Combustion CO₂ Capture**

Technical Approach

- Design and construct pilot-scale unit and obtain parametric data to determine key scale-up parameters
- Perform an EH&S and technical and economic assessment to determine feasibility of commercial scale operation
- Develop scale-up strategy

Outcomes

- Strategy for future scale-up
- Technical and economic feasibility determined
- Environmental assessment

Anticipated Benefits of the Proposed Technology

- 90% CO₂ Capture
- \$40/tonne CO₂ capture cost

• Continuation of previous DOE/NETL funded project (DE-FE0007502)

Scope

This project is divided into two phases.

Phase I: 1/1/2014 - 12/31/2014

(\$1.5MM with 20% GE cost share)

- ✓ Develop preliminary process models and perform preliminary techno-economic analysis
- ✓ Perform preliminary EH&S risk assessment
- ✓ Design and construct pilot-scale aminosilicone desorber skid

Phase II: 1/1/2015 - 6/30/2016

(\$4.2MM with 20% GE cost share)



- Integrate skid with the NCCC pilot-scale system
- Perform pilot-scale testing (**test moved from Spring 2015 to October 2015**)
- Analyze data from pilot tests at 0.5 MW scale
- Perform techno-economic analysis and update cost of carbon capture
- Perform technology EH&S risk assessment
- Develop cost estimate for full-scale manufacture of solvent

Summary of Aminosilicone Advantages


- Lower volatility
 - Simplified separations
 - Less energy wasted vaporizing solvent and/or water
 - Lower airborne release rates
- Lower heat capacity
- Higher thermal stability (higher desorption T/greater capture capacity and/or pressure)
- Reduced corrosion
- Potentially decreased issues with aerosol formation

Aminosilicone Absorbent

GAP-X (Liquid)




GAP-X Carbamate (Solid)




GAP-1_m Absorbent Composition

- 40% GAP-0
- 33% GAP-1
- 19% GAP-2
- 8% GAP-3







Carbamate does not precipitate in a 60/40 (wt/wt) GAP-1_m/TEG mixture









Technical Risks



Corrosion Studies (Stainless Steel)

Location / Metal Type	Conditions	Unexposed samples	Exposed samples
Lean Storage / 304L	~380 hours at ~34 °C and ~6138 hours at ~25 °C		
Absorber Sump/ 304L	~389 hours at ~52 °C and ~6138 hours at ~25 °C		
Desorber / 304L	~388 hours at ~145 °C and ~6138 hours at ~25 °C		

Corrosion Studies (Carbon Steel)

Location / Metal Type	Conditions	Unexposed samples (interface images)	Exposed samples (interface images)
Lean Storage / C1018	~380 hours at ~34 °C and ~6138 hours at ~25 °C		
Absorber Sump / C1018	~389 hours at ~52 °C and ~6138 hours at ~25 °C		
Desorber / C1018	~388 hours at ~145 °C and ~6138 hours at ~25 °C		


Corrosion Studies

- Significant corrosion only seen with carbon steel under desorber conditions
- Carbon steel should be fine for other process components

Sample	Corrosion rate ($\mu\text{m}/\text{yr}$)
C1018 – lean storage	1.27
C1018 – absorber	0.47
C1018 – desorber	2188
304L – lean storage	0.31
304L – absorber	0.53
304L – desorber	-0.50


Process Modeling

- Data from the bench-scale system were used to tune bench-scale carbon-capture model in ASPEN Plus
 - Model scaled up to pilot- and 550 MW commercial-scale
- Process modeling of the coal-fired power plant was performed in Thermoflow by GE Power and Water
 - Model without carbon capture was tuned to match Case 11 from Bituminous Baseline Study
- Power plant model and carbon capture model were integrated




- Base Case – Desorber at 140 °C and 4 bar(a)
- Capture Plant Optimization - Optimization of desorber T, absorber column intercoolers, packing type, etc.
- Power Plant Integration – Cooling water integration and waste heat recovery

First Year Removal Cost of CO₂



Pilot-Scale Process

The NCCC PSTU



- Ability to measure solvent loss
- Operation with real flue gas
 - SO_x, NO_x, heavy metals
- Skid controls integrated with PSTU DCS
- Solvent sampling points
- Corrosion coupon testing locations

Pilot-Scale Skid Design and Fabrication



- ✓ Detailed Engineering Package complete
- ✓ Skid construction is complete
- ✓ Solvent delivered to NCCC
- Working with the NCCC to complete
 - ✓ Detailed HAZOP (completed 12/4/14)
 - Integration of skid with PSTU



Pilot-Scale Skid




Bubble Point Measurements



Bubble Point Measurements

- Heated pressure cell with syringe pump and window
- Set temperature and adjusted pressure until boiling occurred
- Bubble point data is critical to determining acceptable operating conditions for the rich/lean heat exchanger (120 °C and 275 psig)
 - Bubble formation can damage equipment and reduce heat transfer



Future Work

- 2015-2016
 - Integrate skid with PSTU at the NCCC
 - Perform tests (~2 months)
 - Use data to update process models
 - Update Techno-Economic Analysis and EH&S Risk Assessment
- Beyond
 - Determine next scale for testing
 - Look for partners
 - Test site
 - Solvent manufactures
 - Need to grow solvent supply

Thanks

- Andrew O’Palko (program manager)
- Lynn Brickett
- GE GRC team members
- GE Power and Water
- The National Carbon Capture Center

Acknowledgment: This material is based upon work supported by the Department of Energy under Award Number DE-FE0013755.

Disclaimer: This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.