

SMART GRID
FEEDER AUTOMATION
*A DEVELOPMENTAL
FIELD TEST*

Presented by: Thomas Grabowski, Modern Grid Team
EEl Transmission, Distribution and Metering Conference
April 7, 2009



Funded by the U.S. Department of Energy,
Office of Electricity Delivery and Energy Reliability



Conducted by the National Energy
Technology Laboratory

This material is based upon work supported by the Department of Energy under Award Number DE-AC26-04NT41817

This presentation was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.



SMART GRID FEEDER AUTOMATION *A DEVELOPMENTAL FIELD TEST*

MODERN GRID
STRATEGY



Presented by:

PATRICK
ENERGY SERVICES



Office of Electricity
Delivery and Energy
Reliability

What is a Smart Grid?

Detects problems and fixes them before they impact quality of service

Incorporates measures, communication, Intelligent Equipment, advanced diagnostics and provides feedback control

Has the ability to re-route power flows, change load patterns, improve voltage profiles, and take other corrective actions

Enables loads and distributed resources to participate in operations

Uses Advanced Technology to improve design and operation with reliability, security, efficiency and safety.



What is the Modern Grid Strategy?



The Department of Energy currently has several initiatives to improve the National Electrical Grid

One of those initiatives is the Allegheny Power Development Field Test: Morgantown, WV

Its purpose is to test off-the-shelf, open architecture technologies to help improve Allegheny Power's customer outage duration



Who is involved?



Project Objectives

Design and install a feeder automation plan

Develop capability to identify and isolate faulted zones

Install a “Weak Tie” between adjacent feeders to automatically restore service

Prove the autonomous operation of an advanced distribution automation system.

Deliver an improvement in electric service reliability.

Develop an application that can be transferred to utilities nationwide.

Employ Intelligent Electronic Devices

Install Smart Grid type sensing and measurement.

Utilize off the shelf/open architecture technologies.



Office of Electricity
Delivery and Energy
Reliability

Goals for Morgantown DFT Phase 1

Improve reliability
indices

Ability to defer or
avoid some planned
capital investments

Improve power
quality

Minimize the outage
labor cost and
duration

Improve the
protective
coordination scheme

Maximize
coordination of field
crews and operation



Office of Electricity
Delivery and Energy
Reliability

Distribution Substation

- Two 138 - 12.5 kV transformers, 33.6 MVA each
- Two Circuits

Circuit 3

- Three normally closed load break switches to form four zones
- Five normally open tie points to adjacent feeders
- 327 distribution transformers

Circuit 4

- Three normally closed load break switches to form four zone
- Five normally open tie points to adjacent feeders
- 341 distribution transformers



Office of Electricity
Delivery and Energy
Reliability

West Run Circuits 3 & 4 Distribution Reliability Indices

SAIDI	2001	2002	2003	2004	2005
West Run #3	19.52	65.84	192.65	198.01	2193.16
West Run #4	27.43	34.15	53.81	102.58	929.5
CAIDI	2001	2002	2003	2004	2005
West Run #3	85.07	55.11	149	655.48	1387.33
Wes Run #4	140.21	164.14	177.41	285.23	1847.76
SAIFI	2001	2002	2003	2004	2005
West Run #3	0.228398	1.189985	1.289199	0.303107	1.580765
West Run #4	0.198227	0.208831	0.303201	0.35942	0.50792

SAIDI – System Average Interruption Duration Index
(Customer Minutes of Interruption/Average # of Customers Served)


CAIDI - Customer Average Interruption Duration Index
(Customer Minutes of Interruption/Average # of Customers Interruptions)

SAIFI – System Average Interruption Frequency Index
(Customer Interruption/Average # of Customers Served)





Office of Electricity
Delivery and Energy
Reliability

Morgantown Circuit 3 and 4





Office of Electricity
Delivery and Energy
Reliability


Circuit Diagram



How it works...




How it works...



A fault occurs in
Zone 2



How it works...




The recloser
completes its three
operation and locks
out

All four zones are
de-energized



How it works...




DA Logic sequence begins

Open Pole top switches

Isolates Zone 2 from the circuit


How it works...




Substation Circuit
Breaker Closes




How it works...




Zone 1 in
now
reenergized




How it works...



Load Break Switch
between Zone 3
and Zone 4 opens




How it works...




Determines capacity
of adjacent circuit
Load Break Switch
between Zone 4

Adjacent Feeder
closes if capacity is
available



Office of Electricity
Delivery and Energy
Reliability


How it works...




Zone 4 is reenergized




How it works...



Load Break Switch
between Zone 3 and
adjacent feeder
closes




How it works...



Zone 3 is reenergized


Zones 1, 3 and 4 are restored



The entire process to reenergize
Zones 1, 3, and 4,
which took me 10 minutes to explain
occurs in 60 seconds or less,
without human involvement.



How it works...




DA Logic continues to monitor adjacent circuits for overloads

Takes corrective action if necessary


Checks for subsequent faults on restored zones



How it works...




The fault in Zone 2 is cleared by crew



Return to normal is initiated by operations personnel

DA Logic automatically returns the circuit to normal configuration


How it works...



Load Break Switch
between Zone 1 and
Zone 2 closes



How it works...



Zone 2 is reenergized




How it works...



Load Break Switch
between Zone 3 and
adjacent feeder
opens




How it works...



Zone 3 is
de-energized




How it works...




Load Break Switch
between Zone 2 and
Zone 3 closes




How it works...



Zone 3 is reenergized



How it works...




Load Break Switch
between Zone 4 and
adjacent feeder
opens




Office of Electricity
Delivery and Energy
Reliability


How it works...



Zone 4 is
de-energized




How it works...



Load Break Switch
between Zone 3 and
Zone 4 closes



How it works...




Zone 4 is reenergized

Circuit is back to normal configuration



Smart Grid Equipment Configuration



Wi-Fi Intelligent Wireless Network

Support the continuous connections and reconfiguration

Maximizes throughput utilization and minimizes latency

Secure data through encryption and authentication

Monitors health of communications backbone

The self-healing nature

Monitors status of all access points via SNMP and PING

Employs Wi-Fi mesh-enabled communications architecture


Relies on standard wireless communications protocols

Provides communications between the reclosers and switches in the distribution circuits





Office of Electricity
Delivery and Energy
Reliability

Wi-Fi Intelligent Wireless Network



**Pole-Mounted Access Point
Cisco Aironet 1510 Mesh Access Point**

**EdgeFrontier Appliance with embedded
EdgeFrontier middleware**



Pole Controller Cabinet


Typical controller cabinet located on Pole directly below DAS Pole-top Switch, contains:

- **Switch Controller**
- **Intelligent RTU**
- **Radio**
- **Battery and charger**




Cooper DAS Switch and Controller

- **Three-phase**
- **Electronically controlled**
- **Vacuum switch**
- **Medium voltage level**
- **Embedded CTs**
- **Solid dielectric system**
- **Remote controllable**




- Fully distributed and network centric
- TCP/IP communication capability
- Cyber security features
- Standard protocol conversion
- I/O data gathering, control and automation functionality.
- Scalable


West Run Smart Grid RTU



Office of Electricity
Delivery and Energy
Reliability



Office of Electricity Delivery and Energy Reliability





Programmable Logic (Current)

- Open Substation-based system
- Uses predetermined scripted sequences
- Provided shortest development time
- Least costly approach
- Most flexible for testing and revision

Robust Application (Phase II)

- Dynamic network model
- Customer Specifics
- Intuitive Interface
- Drag and drop for circuit re-configurations

Distribution Management System (DMS)



Office of Electricity
Delivery and Energy
Reliability


Completing Phase 1

Monitor
Operation of
Phase 1 to
determine if
goals were
achieved

Fine-tune
interoperability
of all
equipment

Optimize
Operator
interaction with
automation
equipment

Phase 1 scheduled for completion in April, 2009



Office of Electricity
Delivery and Energy
Reliability

Phase 2 Development

Provide frequency response and voltage support to the transmission system

Provide peak shaving and load leveling

Improve power quality to 21st century requirements

Improve reliability indices

Integrate under-frequency and under-voltage grid friendly appliances

Integrate advanced metering infrastructure

Expand dynamic feeder reconfiguration to dynamic islanding

Test advanced distribution automation systems

Defer or avoid planned capital investments



Office of Electricity
Delivery and Energy
Reliability

For additional Information, contact

Patrick Energy Services

<http://www.patrickesi.com>

Charles K. Albrecht

734-293-0480

Modern Grid Strategy Team

<http://www.netl.doe.gov/moderngrid/>

304-599-4273 x101



Office of Electricity
Delivery and Energy
Reliability

QUESTIONS

MODERN GRID
STRATEGY



PATRICK
ENERGY SERVICES



Office of Electricity
Delivery and Energy
Reliability