



EERCSM

Critical Challenges.

Practical Solutions.



CO₂ INJECTION MONITORING WITH A SCALABLE, AUTOMATED, SEMIPERMANENT SEISMIC ARRAY (SASSA)

DE-FE0012665

Amanda Livers

Energy & Environmental Research Center

U.S. Department of Energy

National Energy Technology Laboratory

Mastering the Subsurface Through Technology Innovation, Partnerships and Collaboration:
Carbon Storage and Oil and Natural Gas Technologies Review Meeting

August 1–3, 2017




Critical Challenges. **Practical Solutions.**

PRESENTATION OUTLINE

- Project Overview
 - Study area
 - SASSA concept
- Reservoir Simulations and 2-D Line
- Array Design and Acquisition
- Data Processing and Interpretation
- Accomplishments
- Lessons Learned
- Synergy Opportunities
- Summary




STUDY AREAS AND TARGET



Bell Creek Oil Field

SASSA CONCEPT

- Applying the seismic method to track CO₂ movement in the reservoir.
 - Sparse array and one stationary source.
 - Monitor discrete locations in the reservoir (weekly).
 - Changes to the reservoir reflection character may indicate the passing of CO₂.
 - Validation with dynamic reservoir simulations and 2-D time-lapse seismic.
- Why: Incremental results, actionable information, low impact, possibly cheaper cost, relocate and reuse.



Reservoir Layer





EERC SB51472.CDR



SEISMIC SOURCE

- **Gisco ESS 850**

- 850-lb (385-kg) weight accelerated with a slingshot.
- Powerful, flexible, electrically powered.
- Safe remote operation within a locked structure.



RECORDING SYSTEM

- **Fairfield Zland system**

- 96 autonomous nodes – three-component 5-Hz geophones.
- Programed to wake and receive data on weekends.
- Handheld units for node deployment, GPS location, and mapping.
- Data Management server.
- Charger and data download racks.

EERC SB51489.CDR

Zland
3-Component
Node



Handheld
Terminal



Seismic Management System




EERC SB51466.CDR


DATA QUALITY

- 2-D data have reflection characteristics similar to the conventional 3-D survey in the same area.
- Reflections from the reservoir are weak or intermittent in this area.

SASSA 2-D Baseline




Bell Creek 3-D Baseline – Nearest Inline




ARRAY LAYOUT

- Monitoring focuses on four injector–producer patterns covering about 1 square mile.
- Orange dots represent monitored points.





ARRAY LAYOUT

- Monitoring focuses on four injector–producer patterns covering about 1 square mile.
- Orange dots represent monitored points.
- Blue triangles represent receiver locations.





DETERMINING RECEIVER LOCATIONS

- Because of dip and structure, locating receivers required...
- 3-D velocity modeling:
 - Layered velocity model based on 3-D seismic depth volume
 - Lidar elevation data
- Iterative ray-tracing to locate geophone positions that illuminate the desired reflection point locations.




ARRAY DATA ACQUISITION

- 41 data sets harvested.
- Some data collections missed because of:
 - Internet outage.
 - Equipment repair.
 - Abstention due to weather.
- Source fired remotely ~50 to 100 times.
 - Increased signal-to-noise through vertical stacking.
 - Receiver domain processing prior to stacking.




SOURCE REPEATABILITY

Near-Field Source Signature over Time




MULTIDOMAIN APPROACH


Common Azimuth




Common Azimuth Gather




Pseudo Inline and Crossline




Common Receiver Gather



Inline A



Crossline D



RECEIVER DOMAIN PROCESSING





Channel 92

Raw Data

Processed Data

Vertical Stack

Stacked Trace Repeated



Simple Processing Flow:



- Spherical divergence
- Trace editing
- Bandpass (4-8-56-64-Hz)
- 30-Hz notch

TIME-LAPSE DIFFERENCING

Channel 32


Difference Display

Week Number →




TIME-LAPSE DIFFERENCING

Channel 92




Difference Display
Week Number → 05/07/16




TIME-LAPSE DIFFERENCING

Channel 24




Difference Display


Week Number →



COMPLEMENTARY TIME-LAPSE ANALYSIS



- Levin 4-D quick look method
 - Calculation and comparison of shaping filters





Levin, S. A., 2010, Systems and methods for monitoring time-dependent subsurface changes: U.S. Patent 7,843,766 B2.

Levin, S. A., 2009, 4-D: from mainstream to Main Street: Presented at the Society of Exploration Geophysicists Houston 2009 International Exposition and Annual Meeting, Houston, Texas, October 26–30, 2009.

LEVIN METHOD TEST

- To test the Levin method and refine parameters, it was applied to a 4-D time-lapse crossline known to encounter areas with and without CO₂.


Crossline 179 Difference Display




Time-lapse difference map of the reservoir displaying RMS amplitude changes.

LEVIN METHOD RESULT ON 3-D CROSSLINE


Crossline 179
Difference
Display



Shaping Filter




Shaping Filter
Center Sample
Amplitude




DYNAMIC RESERVOIR SIMULATIONS

- Predictive simulations of CO₂ saturation using Computer Modelling Group (CMG) software to corroborate and help evaluate SASSA results.
- 2-D line for validation appears to skirt the saturation fronts.




TIME-LAPSE DIFFERENCING

Channel 85



Difference Display
Week Number → 04/03/16






APPLICATION OF LEVIN METHOD

Channel 92

Difference Display





Week Number → 05/07/16



KEY CONSIDERATIONS


- Main factors contributing to the success of the SASSA method
 - Source repeatability
 - Noise attenuation
 - Identification of time-lapse changes not associated with changes in CO₂ saturation

Horizon Interpretation



Changing Noise

Seasonal Changes



ACCOMPLISHMENTS TO DATE

- **System implementation and data acquisition complete**
 - Equipment was procured – seismic source, recording system, remote control system, source structure and footing hardware. Geophysical modeling software and data processing software were purchased.
 - Source location was selected – geophysical modeling was completed, monitor locations (midpoints) chosen, and receiver locations determined.
 - Physical system was implemented in the field. Source structure and footing built, 2-D baseline acquired, semipermanent main array installed.
 - Baseline data acquired prior to CO₂ injection. Monitor data acquired on a weekly schedule for 1 year and periodically harvested.
 - Final monitor 2-D line acquired. System retrieved and stored for next use.

ACCOMPLISHMENTS TO DATE

- Data collection, processing, interpretation, and validation
 - Data collection is complete – 41 weeks of data collected.
 - 2-D baseline and monitor seismic data acquired, processed, and interpreted.
 - Wells in the study are history-matched and predictive simulations computed, providing an indication of where CO₂ saturations exist in the study area.
 - Processing workflow developed, refined, and applied. Several innovations have been devised to working with this unique data set, including...
 - Common receiver gather processing
 - Azimuth gathers
 - Pseudo inlines and crosslines
 - The Levin 4-D quick look method to computationally assist in identifying gas-affected locations
 - In-depth analysis and validation of the results are in progress.

ACQUISITION LESSONS LEARNED

- **Ground roll presented a data-processing challenge.**
 - Interferes with reflections on nodes offset <2200 feet from the source.
- **General noise levels varied from week to week and required counteraction.**
 - Wind is a big variable – burying the nodes and shooting earlier in the day may help.
 - Gauging current weather conditions before shooting would be an advantage. Rain is noticeable.
 - More cultural noise occurred than expected. Power line noise, pipeline noise, and pump motor noise near producing wells have presented challenges.
 - Individual nodes require individual attention based on noise proximity.
- **The source shed was protected with a lightning rod, but not from a voltage surge.**
 - An overvoltage surge entered on the power wires, traveled along the battery charger cables, and damaged ALL electronics connected to the source batteries, and more through an Ethernet port.
 - Note: Fuses protect against CURRENT surges, not overvoltage conditions.
 - If the chargers were plugged into the UPS, damage would have been limited to the UPS.
 - The source signature recorder memory was corrupted by the surge. Best practice would be to harvest shot data after each weekly salvo to eliminate data lost to SSR damage.

SYNERGY OPPORTUNITIES

- Several international CO₂ storage projects are experimenting with fixed sources and permanent or semipermanent receiver arrays.
 - Aquistore (Canada)
 - Otway (Australia)
 - Tomakomai (Japan)

Lessons learned from each may be applicable.

- Complementary monitoring method used in combination with the CO₂ EOR monitoring using the Krauklis wave presented later today.

SUMMARY

- Key findings
 - Results are not black and white, but confidence is high that the data show changes due to CO₂.
 - Reservoir simulations show where effort should be concentrated.
 - Ambiguity in identifying changes due to CO₂ exists because of noise levels.
 - Solutions involving data-processing techniques and interpretation methods are being explored to remove ambiguity.
- Future plans
 - Finalize analysis, and validate if possible. Prepare the final report.
 - Submit for publication findings from the study to a scientific journal.

ACKNOWLEDGMENTS

- Thank you to...
 - Denbury Onshore LLC: for field access and assistance in the Bell Creek Field.
 - CGG GeoSoftware: for the donation of HRS-10 software that was used in generating some of the results for this project and presentation.
 - DOE Project Management: Andrea McNemar
 - EERC Geophysics Team: Shaughn Burnison, Olarinre Salako, and Cesar Barajas-Olalde.
 - EERC Oversight and Advisory: John Hamling and Charlie Gorecki.
 - Staff at the EERC including senior management, project management, technical staff, field teams and field support, project support, legal and contracts, procurement, travel, administration, IT, graphics, editing, and more.
- This material is based on work supported by the U.S. Department of Energy National Energy Technology Laboratory under Award No. DE-FE0012665.

This material is based upon work supported by the U.S. Department of Energy
National Energy Technology Laboratory under Award No. DE-FE0012665.

Disclaimer

This presentation was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government, nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

CONTACT INFORMATION

Energy & Environmental Research Center
University of North Dakota
15 North 23rd Street, Stop 9018
Grand Forks, ND 58202-9018

www.undeerc.org
701.777.5344 (phone)
701.777.5181 (fax)

Amanda J. Livers
Research Geophysicist
alivers@undeerc.org



APPENDIX

- Benefit to the Program
- Project Overviews, Goals, and Objectives
- Organization Chart
- Gantt Chart
- Bibliography

BENEFIT TO THE PROGRAM

- Program goals addressed:
 - Develop and validate technologies to ensure 99% storage performance.
 - Develop technologies to improve reservoir storage efficiency while ensuring containment effectiveness.
 - Develop best practice manuals for monitoring, verification, accounting, and assessment.
- The SASSA method is a novel application of existing technology with the potential to track the location of a CO₂ saturation front in the subsurface in a timely and cost-effective manner:
 - To improve measurement and accounting of storage performance.
 - Provide a means of remotely detecting out-of-zone migration of CO₂ (ensuring containment effectiveness).
 - Contribute to best practices for monitoring, verification, and accounting (MVA).

BENEFITS STATEMENT


The project will address Area of Interest 1, “Tools and technologies that provide accurate, high-resolution measurement of CO₂ saturations, plumes, and pressure fronts in the subsurface,” by using commercially available technology to create an innovative, scalable, automated monitoring system for the purpose of detecting the movement of a CO₂ plume and pressure front resulting from the injection of CO₂ into the subsurface. The project goals will be accomplished by deploying the proposed technology at an existing commercial CO₂ enhanced oil recovery and storage project. The results of this effort will validate the use of existing technology to effectively monitor the migration of CO₂ in the subsurface in a cost-effective, noninvasive (both to the environment and the operator) way. These results will contribute to the Carbon Storage Program’s goal of developing and validating technologies to measure and account for 99% of injected CO₂ in the injection zones.

PROJECT OVERVIEW

GOALS AND OBJECTIVES

- Demonstrate and evaluate a novel seismic deployment method that can be operated remotely (and potentially automated) to show where and when a carbon dioxide (CO₂) miscible front passes a particular subsurface location.
- Goals
 1. Install a semipermanent seismic system in the field that includes a safe and remotely operated seismic source.
 2. Collect and process data records to identify time-lapse changes that can be verified as being due to the presence of CO₂.


ORGANIZATION CHART



EERC CG47421.CDR

Figure 1. Project organization chart.

GANTT CHART



Summary Task

Activity Bar

Milestone (M)

Deliverable (D)

Critical Path

| Key for Deliverables (D) ▼ | Key for Milestones (M) ◆ |
|--------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------|
| D1 – Updated Project Management Plan (PMP) | M1 – Project Kickoff Meeting Held |
| D2 – Interim Report on Completion of Technical Design | M2 – Source Location Preparation Initiated |
| D3 – Technical Paper or Journal Article Based on Processing and Modeling Results and Overall Recommendations | M3 – Start Optimization and Testing of Equipment |
| D4 – Final Report | M4 – First Data Available for Processing |
| | M5 – Data Collection Completed |
| | M6 – Comparison to Conventional Seismic and History Match to Geological Model and Simulation Initiated |
| | M7 – Data Processing Completed |

Revision – July 27, 2016

BIBLIOGRAPHY

Barajas-Olalde, C., Livers, A.J., Burnison, S.A., Hamling, J.A., and Gorecki, C.D., 2017, Estimating time-lapse near-surface velocity models using ground roll from coarsely sampled 2-D land crooked surveys: To be presented at the EAGE 23rd European Meeting of Environmental and Engineering Geophysics, Malmo, Sweden, September 3–7, 2017.

Burnison, S.A., Livers, A.J., Hamling, J.A., Salako, O., and Gorecki, C.D., 2016, Design and implementation of a scalable, automated, semi-permanent seismic array for detecting CO₂ extent during geologic CO₂ injection: Presented at the 13th International Conference on Greenhouse Gas Control Technologies, GHGT-13, Lausanne, Switzerland, November 4–18, 2016. Energy Procedia [in press].

Burnison, S.A., Beddoe, C.J., Glazewski, K.A., Salako, O., Hamling, J.A., Ayash, S.C., and Gorecki, C.D., 2015, Technical design of a scalable, automated, semipermanent seismic array (SASSA) method for detecting CO₂ extent during geologic CO₂ injection: Deliverable D2 Interim Report on Completion of Technical Design (Oct 1, 2013 – Oct 31, 2015) for U.S. Department of Energy National Energy Technology Laboratory Cooperative Agreement No. DE-FE0012665, Grand Forks, North Dakota, Energy & Environmental Research Center, October 2015.



THANK YOU!



EERCSM

Critical Challenges.

Practical Solutions.