Pilot Plant Testing of Piperazine (PZ) with High T Regeneration

Gary T. Rochelle (PI) & Eric Chen The University of Texas at Austin

Katherine Dombrowski (PM), URS

Andrew Sexton (TE), Trimeric

Bruce Lani, DOE PM

Outline

- Project overview
- Energy Features of the PZ process
 - A new flash stripper
- Solvent management with PZ
 - Solution analyses from 3 pilot plants
- Future work on aerosol formation
 - A major challenge for volatile amine
- PZ, a competitive alternative

Project Objectives

Primary:

 Quantify robustness of PZ in an integrated system with 150°C regeneration

Secondary:

- Optimize equipment design & energy performance of advanced flash regeneration
- Identify & resolve issues with process control, foaming, solids precipitation
- Evaluate technical & economic feasibility of full-scale implementation

Project Funding

- DOE funded \$3 million
 - Started 10/2010
 - 2-phase project
- \$876k cost-shared by UT CO₂ Capture Pilot Plant Project
 - EPRI
 - Luminant, Southern, LG&E-KU
 - B&W, Chevron

Pilot Plant Testing with PZ

- UT Separations Research Program (SRP)
 - 0.1 MW air/CO₂
 - 10/2011, 3 week operation (DOE Task)
 - 10/2013, 3 week operation (DOE Task)
- Pilot Plant 2 (PP2)
 - Operated in 2011 on coal flue gas
- CSIRO- Tarong (supported by ANLEC)
 - Operated 3 months in 2013 on 0.1 MW coal
- DOE National Carbon Capture Center
 - DOE Task
 - To be Operated 3 months on 0.5 MW coal (2014-15)₅

Piperazine: Superior for Energy

Amine	m	kg'avg*1e7	capacity	$-\Delta H_{abs}$	T _{max}	P _{max}
		mol/s·Pa·m ²	mol/kg	kJ/mol	С	bar
PZ	8	8.5	0.75	73	163	20
AMP/PZ	4_2	8.6	0.80	77	127	5.7
MEA	7	4.3	0.62	77	121	4.0
SarK	6	5	0.27	64	121	2.4


Total Equivalent Work

$$W_{reboiler} = 0.75Q_{flash} \frac{T_{flash} + 5 - T_{sink}}{T_{flash} + 5}$$


$$W_{\text{total}} = W_{\text{reboiler}} + W_{\text{comp}} + W_{\text{pump}}$$

$$W_{comp}\left(\frac{kJ}{mol\ CO_2}\right) = \begin{cases} 4.572 \ln\left(\frac{150}{P_{in}}\right) - 4.096 & P_{in} \le 4.56\ bar \\ 4.023 \ln\left(\frac{150}{P_{in}}\right) - 2.181 & P_{in} > 4.56\ bar \end{cases}$$


Flash Stripper with Rich Exchanger Bypass



Stripping 8 m PZ at 150°C



Energy is approaching a practical limit



PZ: Superior for Solvent Management

- PZ is resistant to oxidation.
 - At absorber conditions (mM/hr)

PZ < 0.15 MEA – 2


- With dissolved metals & O₂ PZ oxidizes at >130°C
- PZ volatility is just right.
 - At lean abs conditions (ppm)


PZ - 8 MEA - 30

- Thermal reclaiming removes nonvolatile impurities
- PZ condenses out aerosols in the absorber
- Nitrosamine is manageable.
 - PZ + NO₂/NO₂⁻ → mononitrosopiperazine (MNPZ)
 - Decomposes at 150°C with stoich oxidation of PZ to leave only 1 mM MNPZ at steady state

Degradation Products (mmol/kg) in PZ pilot plants at 1300 to 1700 hrs

Component	SRP	PP2	Tarong	
Total Formate	2.4	76.6	110.2	
2-PZOH	25.8	71.6	56.0	
NitrosoPZ	0.09	1.2	2.4	
Fe ²⁺	0.02	1.15	0.54	
Other metals	0.04	4.22	0.07	
Nitrate	0.1	4.8	21.8	
Sulfate	0	7.1	26.9	






Amine Aerosol - a Major Challenge

- Nucleation sites in flue gas
 - $-SO_3/H_2SO_4$
 - -Submicron fly ash
- + Droplet growth
 - Amine/CO₂ moves from solvent to aerosol
 - Water condensation
- + Poor droplet collection in water wash
- = Unacceptable amine emissions

Aerosol Grows by PZ Diffusion



Planned Aerosol Testing SRP Pilot plant, Air/CO₂, Fall 2013

- Inject vaporized H₂SO₄ to vary aerosol
- Measure
 - Amine with FTIR using heated sample point
 - Drop Size with Phase Doppler Interferometry
- Grow aerosol in absorber packing
- Collect aerosol in impingement tray

Future Work with 150°C PZ

- Fall 2013 SRP campaign
 - Flash Stripper with 2 bypasses
 - Aerosol characterization & collection
 - Oxidation management
 - Absorber intercooling
 - Reclaiming
- Fall 2014 NCCC

Conclusions

- 8 m PZ with 150°C advanced flash stripper is a promising new baseline capture technology
 - 190 kWh/ton CO₂ (7%<simple stripper)
 - 61% Increase in COE (\$58/tonne CO₂)
 - No significant thermal degradation
- PZ oxidation and nitrosation are manageable
 - Oxidation appears to degrade < 2%/wk
 - Nitrosamine reaches steady-state at 1-2 mM
- PZ aerosol emissions will be addressed in SRP pilot plant, Fall 2013

- ANLEC: Pilot plant samples from Tarong were provided by CSIRO. CSIRO acknowledges financial assistance from Australian National Low Emissions Coal Research and Development (ANLEC R&D). ANLEC R&D is supported by Australian Coal Association Low Emissions Technology Limited and the Australian Government through the Clean Energy Initiative.
- Acknowledgement: "This material is based on work supported in part by the Department of Energy under Award Number DE-FE0005654."
- **Disclaimer:** "This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof."



www.GHGT.info

GHGT-12

October 5 - 9, 2014 | AUSTIN, TX - USA