

*Session: Pre-Combustion Capture Projects*

# **Development of Pre-Combustion CO<sub>2</sub> Capture Process Using High-Temperature PBI Hollow-Fiber Membranes**

Indira S. Jayaweera

Sr. Staff Scientist and CO<sub>2</sub> Program Leader


SRI International

June 23-June 26, 2015 • Sheraton Station Square • Pittsburgh, Pennsylvania



# **Project Overview and Technology Background**

# Why the High-Temperature Membrane Separation of CO<sub>2</sub>?




Note: PBI hollow fiber membrane (HFM) is a H<sub>2</sub>O and H<sub>2</sub> transporting membrane

## Characteristics of PBI Membranes

- PBI has attractive combination of throughput and degree of separation
- Thermally stable up to ~ 300°C and sulfur tolerant
- Tested for 1000 hr at 225°C by SRI

## Advantages of Membrane-Based Separation

- No need to cool syngas
- Reduced CO<sub>2</sub> compression costs
- Emission free, i.e., no solvents
- Decreased capital costs
- Low maintenance



## **SRI**

PBI Membrane Fabrication Research  
Membrane Testing

## **PBI Performance Products, Inc.**

PBI Manufacturer

## **Generon**

Membrane Fabrication Scale-up  
Module Fabrication

## **Enerfex**

Membrane System Modeling

## **Energy Commercialization**

Commercialization Analysis

## **NCCC**

Gasifier Facility Test Site

## **EPRI**

Electric Power Industry Perspective

## **NETL**

Funding and technology oversight

- **Cooperative agreement grant with U.S. DOE-NETL**
- **Period of Performance:**
  - Budget Period 1: 4-30-2014 through 10-31-2015
  - Budget Period 2: 11-01-2015 through 01-31-2017
- **Project Startup Meeting: 06-9-2014**
- **Funding:**
  - U.S.: Department of Energy: \$2.25 million
  - Cost share: \$0.56 million
  - Total: \$2.81 million
- **NETL Project Manager:**
  - Ms. Elaine Everitt

## **Program Objective:**

To develop polybenzimidazole (PBI) membrane-based H<sub>2</sub>/CO<sub>2</sub> separation technology for Integrated Gasification Combined Cycle (IGCC) power plants that shows significant progress towards meeting the overall DOE Carbon Capture Program performance goal of 90% CO<sub>2</sub> capture rate at a cost of \$40/tonne of CO<sub>2</sub> captured by 2025.

## **Project Objectives:**

Obtain sufficient *bench-scale data* for high-temperature PBI polymer membrane separation of pre-combustion syngas to H<sub>2</sub>-rich and CO<sub>2</sub>-rich components. Utilize the data to evaluate the technical and economic viability of PBI-based membrane separation system to achieve NETL's Capture Program Performance Goals.

| Task # | BP    | Task                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Status   | Comments |
|--------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|----------|
| 1      | 1 & 2 | Project management                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | On-Going | On-track |
| 2      | 1     | <ul style="list-style-type: none"> <li>Advanced development of asymmetric hollow fiber spinning</li> <li>Spinning defect-minimized fibers at km lengths</li> <li>Assembling of multi-fiber modules 1-in, 2-in, 4-in modules</li> <li>Installation of sub-scale fiber module test unit in laboratory</li> <li>Conduct laboratory tests to generate parametric performance test database</li> <li>Modeling of membrane performance</li> <li>Technology transfer to initiate industrial scale fiber spinning</li> <li>Design modification of the 50-kW<sub>th</sub> skid design to house commercial membrane modules</li> </ul> | On-Going | On-track |
| 3      | 2     | Modification of the 50-kW <sub>th</sub> test unit and installation at NCCC for the field tests                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |          |          |
| 4      | 2     | Test the skid in a field setting using 50-lb/hr syngas stream from the gasifier at the NCCC and measure membrane performance                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |          |          |
| 5 & 6  | 2     | <ul style="list-style-type: none"> <li>Process techno-economic analysis (TEA) for ~550 MWe Plant;</li> <li>Environmental health and safety (EH&amp;S) analysis</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                    |          |          |
| 7      | 2     | Decommission the system                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |          |          |

***Critical Challenge:***


***Adapting spinning procedures used for fabricating standard polymeric hollow-fiber membranes to this high-temperature polymer***

## Required membrane architecture for gas separation

- Thin dense layer for gas separation
- Porous support for structural strength to stand high pressures


## Composite membrane

- Membrane dense layer and porous layer are two different materials (e.g., polymer on porous metal)
  - **Benefits**
    - Ideal for proof of concept
  - **Limitations**
    - High cost of materials
    - Large footprint
    - Limited permeation



## Asymmetric integral structure

- Fiber is made of one material
  - **Benefits**
    - Low cost
    - Small footprint
    - Easy system scale up
  - **Challenges**
    - Longer fiber-development time










# Fibers Developed Under Previous DOE Program




Energy and Environment Cent

- Development of PBI polymer membrane to replace the original concept that used the PBI-coated porous stainless steel tubes.
- Development of new PBI formulation, installation of a spinning line, and defect free fiber spinning with  $\sim 1 \mu\text{m}$  dense layer (process patent pending).



Measured  $\text{H}_2/\text{CO}_2$  selectivity and  $\text{H}_2$  permeance at 225°C for over 1000 hr.



High-temperature/high-pressure PBI membrane performance for  $\text{H}_2$  separation from syngas

- Membrane stability over 1000 hr was demonstrated.
- $\text{H}_2/\text{CO}_2$  selectivities and their permanence data established for 1- $\mu\text{m}$  dense layer.




A significant achievement in fiber development was made under DE-FC26-07NE43090



# **Progress and Current Status**

## Installation of the second spinning line ~ 1 km/day capacity



SRI-formulated dope  
made from  
commercial PBI  
(available from PBI  
Performance  
Products, Inc.)

**1 kg**

yields




**1 km**

Main Focus: Quality Control

## Installation of the second spinning line ~ 1 km/day capacity

Scratch on the fiber surface showing the dense layer and the open porous support structure underneath



Second Spinning System



SRI-formulated dope made from commercial PBI (available from PBI Performance Products, Inc.)

**1 kg**

yields



**1 km**

Main Focus: Quality Control




# High-Magnification Pictures of New Fiber Cross Sections



Energy and Environment Cent


~ 0.1  $\mu\text{m}$  dense layer



- We have developed protocols for spinning  $< 0.3 \mu\text{m}$  micron dense layer hollow fiber membranes with membrane OD 450 to 650  $\mu\text{m}$ . Pictures shown are for  $\sim 0.1 \mu\text{m}$  fibers with  $\sim 600 \mu\text{m}$  OD.
- Fabrication of hollow-fiber membrane with a very thin dense layer ( $< 0.3 \mu\text{m}$ ) in kilometer lengths with very good reproducibility
- Testing of over 30 1-in fiber bundles for fiber spinning optimization
- Spinning ( $>30 \text{ km}$ ) and shipping of  $\sim 10 \text{ km}$  of fiber to Generon to fabricating a 2-in module for initial testing of the prototype skid

# Fiber Performance Testing

**Prototype test unit  
setup at SRI site  
~ 1 kW<sub>th</sub> capacity  
(~ 0.16 m<sup>2</sup> fiber  
surface area)**



**Data acquisition**




**Feed gas**



**Potted fiber  
bundles with  
14-in length,  
100 fibers, and  
high packing  
density**


- Single gases tested: CO<sub>2</sub>, H<sub>2</sub>, CO and N<sub>2</sub>
- Gas mixtures tested: CO<sub>2</sub>/H<sub>2</sub>, CO<sub>2</sub>/H<sub>2</sub>/N<sub>2</sub>, CO<sub>2</sub>/H<sub>2</sub>/CO and CO<sub>2</sub>/H<sub>2</sub>/CO/N<sub>2</sub>
- Parameters varied: T, ΔP, composition, stage cut

# Gas Permeation Results from Single Gas Testing: Effect of Temperature and Pressure



Measured permeance of H<sub>2</sub> and CO<sub>2</sub> through a <0.3 μm dense layer fiber bundle as a function of temperature and differential pressure.


# Single-Gas Testing: Effect of Temperature and Pressure



| Selectivity                      |       |
|----------------------------------|-------|
| H <sub>2</sub> /CO <sub>2</sub>  | 40    |
| H <sub>2</sub> /N <sub>2</sub>   | 98    |
| H <sub>2</sub> /CO               | 103   |
| H <sub>2</sub> /H <sub>2</sub> S | >200* |


225 C and 200 psi ΔP

\* Previous work



Dense layer ~ 2 μm

H<sub>2</sub>/CO<sub>2</sub> selectivity = ~ 40  
 H<sub>2</sub> permeance = 70 GPU  
 E<sub>H<sub>2</sub></sub> = 25 kJ/mol



Dense layer ≤ 0.3 μm

H<sub>2</sub>/CO<sub>2</sub> selectivity = 22 ± 2  
 H<sub>2</sub> permeance = 120 GPU  
 E<sub>H<sub>2</sub></sub> = 16.1 kJ/mol

Measured permeance of H<sub>2</sub> and CO<sub>2</sub> through a < 0.3 μm dense layer fiber bundle as a function of temperature and differential pressure. Permeate side at 1 bar


1 GPU = 10<sup>-6</sup> cm<sup>3</sup> s<sup>-1</sup> cm<sup>-2</sup> Hg cm<sup>-1</sup>

Performance monitored over a three-month period with the HFM exposed to -pressure swing at 1 to 15 atm; and temperature swing at 20 ° to 225 ° C.



# Mixed-Gas Testing : Effect of CO<sub>2</sub> concentration



## H<sub>2</sub> and CO<sub>2</sub>



H<sub>2</sub> recovery and CO<sub>2</sub> capture at varying CO<sub>2</sub>/H<sub>2</sub> compositions at 225°C and at a  $\Delta P$  of 200 psi (H<sub>2</sub>/CO<sub>2</sub> selectivity = ~40)

Observation: >95% H<sub>2</sub> recovery is possible without a cascade

# Mixed-Gas Testing: Effect of Selectivity



**Relationship between H<sub>2</sub> separation factor and the kinetic diameter of the component gases.**

**H<sub>2</sub> recovery and CO<sub>2</sub> capture at 225° C and at a ΔP value of 200 psi (stage cut > 0.5)**

Observation:

It is challenging to capture >90% CO<sub>2</sub> at high H<sub>2</sub> recoveries (>95%) with a single element

# Fabrication of Large Modules: 2-in Module



Prototype 2-in module



SRI spun fibers (~ 5 km shown)



2-in module cross-section

Actual 2-in module


- A protocol was developed for potting PBI HFM without dry spots
- The method was tested using SRI fibers (1 m<sup>2</sup>)
- SRI plan to evaluate the performance with H<sub>2</sub>O/N<sub>2</sub> mixtures

## Accomplishments in fiber spinning at SRI have revealed:

- Ways to produce defect-free fibers
- Best use of analytical techniques to determine the trace levels of solvent left in the fibers
- New coagulant for industrial setting

## Accomplishments in fiber spinning at Generon:

- Fabricated 150-200 micron OD, 75-100 micron ID, and macro-void free fibers
  - Currently improving the fiber porosity




## Accomplishments in fiber module fabrication at Generon:

- Fabricated a 2-in module using SRI fibers
- Completed 4-in module design

## Accomplishments in fiber spinning at PBI Performance:

- Produced new formulations for SRI specification in support of Generon and SRI fiber spinning



**Lesson learned:** Implementation of the spinning technology in an industrial setting requires considerable time.


# Key Findings and Accomplishments (Continued)



Energy and Environment Center

- PBI HFMs can be produced at **km lengths** with minimum defects.
- Upper limit for H<sub>2</sub>/CO<sub>2</sub> selectivity is ~ 40.
- Practical H<sub>2</sub>/CO<sub>2</sub> selectivity for laboratory-scale spun fibers is 20-25 with shell-side dense layer
- Membrane test systems reach steady-state operation very rapidly (within few minutes)
- 50 kW<sub>th</sub> skid design completed and fabrication contracted
  - Fabrication will be completed in BP2

## **SRI PBI HFM: 1/4-in Mandrel Test**



# Transition from smaller-module to larger-module testing




## BP1 / BP2


| Module Size                                                                                 | Budget Period | Fiber Supplier/<br>Module Supplier <sup>##</sup> | Test Site      |
|---------------------------------------------------------------------------------------------|---------------|--------------------------------------------------|----------------|
| 2-in x 12-in                                                                                | BP1 and BP2   | SRI/Generon                                      | SRI            |
| 4-in x 20-in <sup>#</sup>                                                                   | BP2           | SRI/Generon                                      | NCCC (50 MWth) |
| 6-in x 40-in                                                                                | BP2           | Generon/Generon                                  | NCCC (50 MWth) |
| <sup>#</sup> : Module design in BP1, Skid design and fabrication in BP1, Skid update in BP2 |               |                                                  |                |
| PBI Dope Supplier: PBI Performance Products                                                 |               |                                                  |                |

## Test unit (50 kW<sub>th</sub>) installation and commissioning at NCCC

- Process safety review and Hazard/Operability (HazOp) Study
- Installation of the test unit at NCCC
- Short term and longer duration testing (225 °C, ~ 200 psi)



# Membrane Performance Simulation for Field Testing



## Membrane parameters

- H<sub>2</sub> Permeance = 120 GPU
- H<sub>2</sub>/CO<sub>2</sub> Selectivity = 25
- Dense layer thickness = 0.3
- Membrane area = 14.6 m<sup>2</sup>

89% CO<sub>2</sub> Capture  
95% H<sub>2</sub> Recovery



**Benchmarked  
against NETL  
simulations**

**Aspen Process Simulation  
& GT Pro Simulation**

**Metric of success  
in meeting  
program goals**

**Economic Analysis  
< 20% increase in COE**

**New data  
from current  
study**

**Updated COE**

**Develop Membrane  
Performance Targets**

25

## Process design and engineering study:

- Determine how the high temperature hollow-fiber PBI membrane process concept would be incorporated into a nominal 550-MWe gasification-based power plant with CCUS.
- Use an IGCC process based on a GE-oxygen-blown gasifier and selexol-based CO<sub>2</sub> removal as the base case.
- Perform the work in collaboration with EPRI

The preliminary estimations show that the CO<sub>2</sub> capture cost for combined process would be ~ \$39 /tonne of CO<sub>2</sub> captured compared to \$52/tonne of CO<sub>2</sub> captured for IGCC with the baseline technology, Selexol.

- **Elaine Everitt (NETL)**
- **SRI Team**
- **Richard Callahan (Enerfex, Inc.)**
- **Kevin O'Brien (Energy Commercialization, LLC)**
- **Greg Copeland (PBI Performance Products)**
- **Mike Gruende (PBI Performance Products)**
- **John Jensvold and his team (Generon IGS)**

This presentation includes an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.



**Technical Contact:**  
**Dr. Indira Jayaweera**  
**Sr. Staff Scientist**  
**CO<sub>2</sub> Program Leader**  
[Indira.jayaweera@sri.com](mailto:Indira.jayaweera@sri.com)  
1-650-859-4042

*Headquarters: Silicon Valley*

**SRI International**  
333 Ravenswood Avenue  
Menlo Park, CA 94025-3493  
650.859.2000

*Washington, D.C.*

**SRI International**  
1100 Wilson Blvd., Suite 2800  
Arlington, VA 22209-3915  
703.524.2053

*Princeton, New Jersey*

**SRI International Sarnoff**  
201 Washington Road  
Princeton, NJ 08540  
609.734.2553

*Additional U.S. and  
international locations*

**www.sri.com**

**Thank You**