

---

The Impact of Scale-Up and  
Production Volume on  
SOFC Stack Cost

Jan H. J. S. Thijssen,

J. Thijssen, LLC, Redmond, WA, USA

Poster Presented At:

7<sup>th</sup> Annual SECA Workshop  
and Peer Review

Date: September 12<sup>th</sup>, 2006

Prepared for:



J. Thijssen, LLC

The logo for J. Thijssen, LLC consists of the company name in a blue, serif font. To the right of the text is a stylized blue graphic of a sun with rays and a wavy line below it, suggesting a sunrise or a wave.

---


4910 163<sup>rd</sup> Avenue NE, Redmond, WA 98052, USA

t: 206 229 6882; e: [jant@jthijssen.com](mailto:jant@jthijssen.com)

## Background & Objective


# Meeting SECA cost targets for SOFC will require technology improvement, mass production, and possibly scale-up.

- Achieving SECA SOFC cost targets (\$400/kW) is critical for market success
- Previous studies quantified the impacts of technology improvements
- Impact of production volume and scale-up hadn't been quantified



**The objective of this study was to quantify the impacts of production volume and stack scale-up on SOFC cost**

# Model Structure and Assumptions



## Key Costing Assumptions


- Production volume: 250 MW/yr
- Capital charge rate: 15% of installed capital
- Auxiliary equipment, installation factors: 80%
- Maintenance cost: 4% of installed capital
- 3 shifts per day
- Manufacturing losses depend on cell geometry and size

## Materials Cost (1 ton/yr)<sup>1</sup>

Ni-YSZ	\$14/kg
YSZ	\$12 / \$25/kg <sup>2</sup>
LSM	\$25/kg <sup>1</sup>
LSCo / LSCF	\$36/kg
Ferritic Stainless <sup>3</sup>	\$5/kg


- 1 Based on DOE and J. Thijssen, LLC estimates
- 2 For >1µm and <1µm average particle size respectively
- 3 Uncoated, e.g. Crofer 22 APU

# Detailed Manufacturing Analysis Cells & Interconnects




# Cell, Stack, and Scale-Up Assumptions<sup>1</sup>

## Ceramic Cell Layer Structure





## Unit Cell Structure



<sup>1</sup> Stacks based on planar, rectangular cells shown here; the study assessed three other stack technologies

# Modular Stack Scale-Up and Manufacturing Approach




1 Stacks based on planar, rectangular cells shown here; the study assessed three other stack technologies

## Ceramic Cell Baseline Cost

# Anode material and fabrication dominate ceramic cell baseline cost

- Anode material, capital, and labor & utilities costs are the main ceramic cell cost components
- Based on  $\sim 400$  mW/cm<sup>2</sup> peak power the cost of cells is around \$90/kW
- Scale-up from 140 to 1700 cm<sup>2</sup> cells:
  - Active cell area increases from 84% to 95% in scale
  - Increased manufacturing losses offset gain (Assuming same # of defects per unit area)




## Stack Baseline Cost

# Ceramic cell anode material and fabrication dominate overall baseline stack cost\*

- Ceramic cell cost dominates stack cost, though interconnect and stack conditioning & QC also contribute significantly
- Based on 400 mW/cm<sup>2</sup> active area stack cost are around \$180 per kW for small cells (current state-of-the-art)
- At the stack level, cell scale-up provides advantages:
  - Cell cost increases slightly
  - Cost of QC, IC, and BOS strongly reduced
- This supports system costs of \$400 - \$600/kW

\* Stack insulation and manifolding are not included






## Impact of Production Volume

### Production volume has a critical impact on SOFC stack cost, especially if production volume is lower than 50MW/yr

- At low volume, fixed costs are high due to poor utilization of capital and labor:
  - Affects mostly ceramic cell and IC
  - BoS can be outsourced and QC requires many parallel units, even at low production volume
- Above 50-100 MW, the benefit of production volume increase diminishes as equipment scale-up and utilization are mostly optimized



## Conclusions

### **High production volume cuts SOFC stack cost more effectively than scale-up**

- The study suggests that the manufactured cost of planar anode-supported SOFC will likely be below \$200 per kW in high volume production
- If production volumes are lower than 50 MW/yr (vs 250 MW/yr) stack cost may be more than \$750/kW
- Cell scale-up has the potential to reduce stack cost by ~25%

## Acknowledgements & References

DOE NETL generously supported this work. Special thanks go out to Wayne Surdoval, Travis Schultz, and Heather Quedenfeld for their feedback, and to Lou Berkshire, and Kevin Moore for their guidance.