



INSTITUTE FOR ENERGY STUDIES
THE UNIVERSITY OF NORTH DAKOTA

Evaluation of Carbon Dioxide Capture From Existing Coal Fired Plants by Hybrid Sorption Using Solid Sorbents

Steve Benson
Srivats Srinivasachar



Presentation Overview

- Project Overview
- Technology Fundamentals
- Project Scope
- Current Status
- Plans for Future Testing



Project Team

- US Department of Energy - NETL
- UND Institute for Energy Studies
- Envergex LLC
- Lignite Energy Council/NDIC
- ALLETE Group
 - Minnesota Power
 - BNI Coal
- SaskPower
- Barr Engineering
- Solex Thermal



Project Objectives

- Develop a process using solid sorbents that will efficiently capture CO₂ from flue gas streams and regenerate into a pure CO₂ stream, with a lower operating cost than current methods.
- Goal: 90 percent CO₂ removal at no more than 35 percent increase in the cost of electricity.
- Combine existing technologies to create a new sorbent which will have high CO₂ loading capacity and a process with low reaction energies.



Budget – Funding Sources

Performance period: 10/1/11 to 09/30/14



0 1,000,000 2,000,000 3,000,000

Total Funds = \$3.69 Million



Background on the Proposed Technology and Scientific/Technical Merit



Technology Background

- The hybrid sorption CACHYSTTM process uses an additive-enhanced regenerable alkali carbonate sorbent for CO₂ capture.


Reactions



- Sorbents prepared from bulk commodity materials – low cost target.
- Reacts with CO₂ to form adduct. Reversible with the addition of heat.
- Additive – increases adsorption kinetics and reduces sorption energy.
- Initial concept testing conducted by Envergex and UND under DOE STTR program.



CACHYS™ Hybrid Sorption Process




CACHYS™ Process Benefits

Benefits

- ✓ Low reaction heat ~ 40-80 kJ/mol CO₂
- ✓ High sorbent capacity
- ✓ Increased sorption kinetics
- ✓ Use of low cost, abundantly available materials

Challenges

- ✓ Confirmation of energetics
- ✓ Confirmation of sorbent capacity
- ✓ Sorbent integrity
- ✓ Sorbent handling



Project Scope



Technical Approach and Project Scope

- Scope of work includes eight main tasks:
 - Task 1: Project Management and Planning
 - Task 2: Initial Technology and Economic Feasibility Study
 - Task 3: Determination of Hybrid Sorbent Performance Metrics
 - Task 4: Bench-Scale Process Design
 - Task 5: Bench-Scale Process Procurement and Construction
 - Task 6: Initial Operation of the Bench-Scale Unit
 - Task 7: Bench-Scale Process Testing
 - Task 8: Final Process Assessment



Decision Points and Success Criteria


Decision Point	Basis for Decision/Success Criteria
Completion of Budget Period 1 Year 1	<ol style="list-style-type: none"> 1. Successful completion of all work proposed in Budget Period 1 2. Demonstrate sorbent CO₂ equilibrium capacity of greater than 70 g of CO₂/kg of sorbent 3. Demonstrate a heat of sorption of 80 kJ/mol of CO₂ or less 4. Submission of a Topical Report – Preliminary Technical and Economic Feasibility Study 5. Submission/approval of a Continuation Application to DOE
Completion of Budget Period 2 Year 2	<ol style="list-style-type: none"> 1. Successful completion of all work proposed in Budget Period 2 2. Submission of a bench-scale engineering design package 3. Complete construction of a bench-scale CACHYS™ system 4. Submission of a test matrix for the bench-scale testing campaign 5. Submission/approval of a Continuation Application to DOE
End of Project Year 3	<ol style="list-style-type: none"> 1. Successful completion of all work proposed 2. Complete continuous testing of integrated bench-scale CACHYS™ process for 1 month 3. Submission of a Topical Report – Final Technical and Economic Feasibility Study 4. Submission of a Topical Report – Preliminary EH&S Assessment 5. Submission of a Final Report



Project Results





Bed Reactor Testing




Components	
A	Mass Flow Controllers
B	Bubbler
C	Air Preheater
D	Steam Generator
E	Reactor
F	Condenser
G	Water Knockout Drum
H	5 Gas Analyzer
I	Manual Steam Control #1
J	Manual Steam Control #2
T1	Thermocouple – Air In
T2	Thermocouple – Reactor Wall
T3	Thermocouple – Air Out
P1	Pressure Transducer (Bottom)
P2	Pressure Transducer (Top)

Bed Reactor Testing Results




CO₂ Adsorption Capacity




CO₂ Adsorption Capacity


6-26-2012 HCK-5 Sorbent




Adsorption-Desorption Cycle: TGA/DSC



CO₂ Sorption Energetics



CO₂ Sorption Energetics



Next Steps

Year 2

- Task 4. Bench-Scale Unit Design
- Task 5. Bench-Scale Unit Procurement and Construction
- Task 6. Initial Operation of the Bench-Scale Unit

Year 3

- Task 7- Bench-Scale Process Testing
- Task 8 - Final Process Assessment



Acknowledgements

- Project Funding and Cost Share
 - DOE-NETL
 - Lignite Energy Council/NDIC
 - ALLETE (Minnesota Power and BNI Coal)
 - SaskPower
 - Solex
 - UND
- DOE-NETL Project Manager – Andrew Jones



Contact Information

Steven A. Benson, Ph.D.

Institute for Energy Studies, University of North Dakota

(701) 777-5177; Mobile: (701) 213-7070

steve.benson@engr.und.edu

Srivats Srinivasachar, Sc.D.

Envergex LLC

(508) 347-2933; Mobile: (508) 479-3784

srivats.srinivasachar@envergex.com



INSTITUTE FOR ENERGY STUDIES
THE UNIVERSITY OF NORTH DAKOTA