

## CO<sub>2</sub> Capture from IGCC Gas Streams Using the AC-ABC Process

2016 NETL CO<sub>2</sub> Capture Technology Meeting  
August 08, 2016 Pittsburgh, PA

Anoop Nagar  
anoop.nagar@sri.com

# Project Overview



- Project Participants:
  - SRI International.
  - Bechtel Hydrocarbon Treatment Solutions, Inc.
  - EIG, Inc.
  - National Carbon Capture Center
  - U.S. DOE (National Energy Technology Laboratory)
- Funding:
  - U.S. Department of Energy: \$5,828,047
  - Cost Share (SRI and BHTS): \$1,662,648
  - Total: \$7,490,695
- Performance Dates:
  - October 2009 through September 2016

# Project Objectives

- Overall objective:
  - To develop an innovative, low-cost CO<sub>2</sub> capture technology based on absorption on a high-capacity and low-cost aqueous ammoniated solution with high pressure absorber and stripper.
- Specific objectives and project status:
  - Test the concept on a bench scale batch reactor (completed)
  - Determine the preliminary optimum operating conditions (completed)
  - Design and build a small pilot-scale reactor capable of continuous integrated operation (completed)
  - Perform tests to evaluate the process in a coal gasifier environment (completed)
  - Perform a technical and economic evaluation on the technology (Updates are in progress)


# Process Fundamentals

- Uses well-known reaction between carbon dioxide and aqueous ammonia :



- Reactions are reversible
  - Absorption reactions at lower temperature
  - Desorption reactions at higher temperature
- High pressure operation enhances absorption of  $\text{CO}_2$
- A similar set of reactions occur between  $\text{H}_2\text{S}$  and ammoniated solution
- $\text{H}_2\text{S}$  from the regenerated gas is converted to elemental sulfur at high pressures

# Process Block Flow Diagram




# Process Highlights

- Concentrated ammoniated solution is used to capture both CO<sub>2</sub> and H<sub>2</sub>S from syngas at high pressure.
- Absorber operation at 40°-60° C temperature; No refrigeration is needed.
- CO<sub>2</sub> is released at high pressure (30 bar) at <200°C:
  - The size of CO<sub>2</sub> stripper, the number of stages of CO<sub>2</sub> compression, and the electric power for compression of CO<sub>2</sub> to the pipeline pressure are reduced.
- High net CO<sub>2</sub> loading, up to 20 wt. %.
- The stripper off-gas stream, containing primarily CO<sub>2</sub> and H<sub>2</sub>S, is treated using a high pressure Claus process, invented by Bechtel, to form elemental sulfur.
  - CO<sub>2</sub> is retained at high pressures.

# Process Advantages


- Low cost and readily available reagent (aqueous ammonia).
- Reagent is chemically stable under the operating conditions.
  - Ammonia does not decompose under the operating conditions.
- High efficiency for CO<sub>2</sub> capture
  - Reduces water-gas shift requirements - Reduced steam consumption.
- No loss of CO<sub>2</sub> during sulfur recovery
  - High pressure conversion; No tail gas treatment
- Low heat consumption for CO<sub>2</sub> stripping (<600 Btu/lb CO<sub>2</sub>)
  - <1.5 GJ/Tonne CO<sub>2</sub>
- Extremely low solubility of H<sub>2</sub>, CO and CH<sub>4</sub> in absorber solution: Minimizes loss of fuel species.
- Absorber and regenerator can operate at similar pressure.
  - No need to pump solution across pressure boundaries. Low energy consumption for pumping.

# Bench scale data - CO<sub>2</sub> Capture Efficiency vs Solution Composition







# Pilot data - CO<sub>2</sub> Capture Efficiency > 99%




# Pilot data – absorption pressure and temperature




# Bench scale data - Rapid Rate of Reaction Approaching Equilibrium




# Pilot data - CO<sub>2</sub> in clean syngas




# Pilot data - H<sub>2</sub>S capture efficiency > 99%




# Bench scale data - Measured CO<sub>2</sub> Attainable Pressure Function of Temperature



# Pilot data – Absorption and Regeneration at high pressure




# Pilot data – Regeneration at moderate temperature







# Pilot data - Steam input for regeneration




# Pilot data – Effective CO<sub>2</sub> loading




# Pilot data - Ammonia emission from absorber




# Pilot data – Regenerated gas stream




# Pilot data – Regenerated gas stream contd.



# AC-ABC Process Schematic



# PFD for the NCCC Test



**SRI International**

301 KAWAUCHI DR. AKA  
MERCER PARK, CO. 60311

BUILDING\_#  
PROJECT\_LOCATION  
PROJECT\_TITLE

PIPING & INSTRUMENT DIAGRAM

SCALE	NAME	NAME1
DATE		
ISS-NO	300-142	
REVISED BY	D-WRICE-142	

P-01

# AC-ABC / BPSC pilot at NCCC



1<sup>st</sup> Test Campaign - August/Sept 2015 – 300 hr. operation  
2<sup>nd</sup> Test Campaign April/May 2016 – 400 hr. operation



# Syngas Compressor and inlet gas manifold



Analytical equipment cabinet, pressurized

- CO<sub>2</sub> measurement
- Ammonia measurement

# AC-ABC columns and skids



Process columns

- SS 316, 8" dia., 40' tall

Process skids

- 5' x 10' – 2 skids



# Electrical, control and data acquisition




Process controllers

Data acquisition system

Pump speed controllers


# Bechtel Pressure Swing Claus (BPSC) Process



# BPSC Process Skid -Columns and sulfur condenser

Catalytic reactors, 4" dia., 10' tall


Condensers



2 Skids – 5' x 10' and 10' x 14'

Elemental sulfur

# AC-ABC and BPSC Process Changes to IGCC Reference Case



# Plant Performance Summary

Plant Performance	Units	IGCC with SRI AC-ABC and BPSC	Reference Case IGCC with CO <sub>2</sub> capture B5B <sup>#</sup>
Gas Turbine Power	MWe	464.0	464.0
Syngas Expander Power	MWe	6.3	6.5
Steam Turbine Power	MWe	243.8	263.5
Auxiliary Load	MWe	162.5	190.8
Net Plant Power	MWe	551.6	543.3
Net Plant Efficiency (HHV)	-	33.1%	32.6%
Net Plant Heat Rate (HHV)	kJ/kWh	10,166	11,034
	Btu/kWh	9,636	10,458

# Cost and Performance Baseline for Fossil Energy Plants, Vol 1b, July 31, 2015, Table ES-2



# Economic Analysis

Economic Analysis (base 2011\$)	IGCC with SRI AC-ABC and BPSC	Reference Case IGCC with CO <sub>2</sub> capture B5B <sup>#</sup>
Total Plant Cost, before Owner's Costs, million	\$1,648	\$1,840
Total Plant Cost, before Owner's Costs	\$2,988/kW	\$3,387/kW
Initial Chemical Fill Cost, million	\$4.90	\$16.50
Annual Fixed O&M Cost, million	\$69.40	\$69.40
Annual Variable O&M Cost, million	\$41.20	\$46.60
Total Annual O&M Cost, million	\$110.60	\$116.00
FY COE* without TS&M**	\$124.46	\$135.56
FY COE with TS&M	\$133.66	\$144.76
COE (% increase from base case IGCC, no CO <sub>2</sub> capture)	30.3 %	41.2 %

\*FY COE = First Year Cost of Electricity

\*\*TS&M = Transport, Storage, and Monitoring

# Cost and Performance Baseline for Fossil Energy Plants, Vol 1b, July 31, 2015, Table ES-4



# Anticipated Benefits

- We estimate a 8.3 MW improvement in Net Plant Power and a 0.5 % point increase in Net Plant Efficiency (HHV basis) than a reference plant (GE gasifier with Selexol AGR and conventional Claus).
- Capital cost is ~10 % less than the reference IGCC plant with CO<sub>2</sub> capture.
- The COE is 7.5 % lower for the SRI AC-ABC/BPSC plant relative to the reference IGCC case with CO<sub>2</sub> capture.
- The process configuration is economically viable per this analysis.

# Acknowledgement

- SRI International
  - Anoop Nagar, Marc Hornbostel, Jin-Ping Lim, Elisabeth McLaughlin, Bill Olson
- EIG:
  - Eli Gal
- Bechtel Hydrocarbon Treatment Solutions:
  - Lee Schmoe, Martin Taylor
- National Carbon Capture Center:
  - Scott Machovec, Patrick Crossley
- DOE-NETL
  - Steve Mascaro

# DISCLAIMER

This presentation was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

# Thank You



**Contact:**

Anoop Nagar

SRI International

650.859.3942

[anoop.nagar@sri.com](mailto:anoop.nagar@sri.com)

*Headquarters: Silicon Valley*

**SRI International**

333 Ravenswood Avenue

Menlo Park, CA 94025-3493

650.859.2000

*Washington, D.C.*

**SRI International**

1100 Wilson Blvd., Suite 2800

Arlington, VA 22209-3915

703.524.2053

*Princeton, New Jersey*

**SRI International Sarnoff**

201 Washington Road

Princeton, NJ 08540

609.734.2553

*Additional U.S. and  
international locations*

**[www.sri.com](http://www.sri.com)**