

nXis - Well Integrity Inspection in Unconventional Gas Wells

DE-FOA-0001076




Matthias Kasten, Ph.D.
General Electric Company



U.S. Department of Energy
National Energy Technology Laboratory
Mastering the Subsurface Through Technology, Innovation and Collaboration:
Carbon Storage and Oil and Natural Gas Technologies Review Meeting
August 16-18, 2016

Presentation Outline

- Project Goals & Objectives
- Technical Status
 - Neutron Modality
 - X(γ)-Ray Modality
 - Ultrasound Modality
 - Electromagnetic Modality
 - Multi-Modality Data Fusion
 - Test Pit Testing
- Accomplishments to Date
- Summary



Benefit to the Program

- Well integrity inspection for multi-casing gas wells to enhance safety and environmental protection.
- Dual-particle imaging technique using neutron and X(γ)-ray backscatter.
- The research project is developing a new dual-particle imaging technique, combining neutron and X(γ)-ray modalities, and algorithmically fusing this data with information obtained from electromagnetic imaging to obtain results which are intrinsically more accurate than the simple union of individual modality results.



Project Overview:


Goals and Objectives

- Measuring the integrity of multiple well casings and cement annuli at intermediate-to-surface depths along major ground water zones.
- Current imaging technologies cannot resolve multiple annuli in the intermediate zone above 10,000 ft. where there are 2 to 5 stacked casing/cement rings.
- Ultrasound-based techniques do not operate reliably in gas filled wellbores.
- Electromagnetic tools are sensitive only to damages in metallic structures. Internal pipe strings magnetically shield external pipes to significantly reduce sensitivity.




Project Overview: Goals and Objectives

Multi-Casing Inspection of Wells Using Fused Multi-Modality Imaging System




Technical Status

Neutron Modality




Neutron Backscatter Experimental Setup



Photographs of integrated neutron generator prototype system (1-11/16" form factor).



Neutron Detector Assembly




MCNP simulation input showing neutron generator, defects, and detector assembly.



Technical Status


Neutron Modality



Phantom with 3"×2.5" diameter defects: cement (no defect), air void, and HD PE.

Detection Results:

- Clear distinction between cement (no defect), air void, and high-density polyethylene (HD PE) for 3" by 2.5" size defect.
- Azimuthal defect detection.





Experimental Data



Technical Status

Neutron Modality



Multi-Annulus Experimental Setup



Technical Status

X(γ)-Ray Modality

Monte Carlo N-Particle (MCNP) Simulation:

Definition of Detectability:


A defect is deemed detectable if the threshold metric of 2σ is met (95% confidence).

Defect:

Air void defects with various diameters (e.g. $\frac{1}{8}$ ")



Source:

X(γ)-Ray source





Technical Status

X(γ)-Ray Modality



Top & side view of detector configuration


MCNP: Air Void Detection in 2nd Casing



Technical Status



X(γ)-Ray Modality

MCNP Simulations: Air Void Detection in 2nd Casing



Technical Status


X(γ)-Ray Modality



Photograph of 1/4" through hole steel-cement-steel void detection experiment.

Detection Results:

- Detection of 1/8" air void in 2nd metal casing and cement annulus (from MCNP simulations).
- Defect detectability up to 3.5" past first casing (from MCNP simulations).
- Azimuthal defect detection.




Backscatter rate vs. defect position for 1/2" and 1/4" blind hole (3mm depth, 50%).

Technical Status

X(γ)-Ray Modality



Multi-Annulus Experimental Lab Setup




Multi-Annulus X(γ)-Ray Detector



Technical Status

Ultrasound Modality


Low Frequency Air-Contact Experiments



"Pitch-Catch" experimental setup



Concrete phantom with air void defects




Detection of air void defects in concrete




Technical Status

Ultrasound Modality


Electro Magnetic Acoustic Transducer (EMAT) Testing



Various test setups used for EMAT evaluation



Photograph of laboratory setup




Small signal variations for SH wave experiment!



Technical Status



Electromagnetic Modality



Production tube inspection with a 1.5" transceiver probe. External area material losses of 20%, 30%, and 40%.

Detection Results:


- Defect detectability (material loss) in 1st casing.
- Eccentricity detectability between 1st and 2nd casing.
- Azimuthal defect detection.




Casing Eccentricity Measurements

Technical Status

Electromagnetic Modality



Eccentricity measurements between 1st and 2nd casing





Signal response for two coils

Signals from multiple coils allow for unique identification of the pipe position/eccentricity.




Technical Status

Multi-Modality Data Fusion




Reshaping of simulated X(γ)-ray image to match electromagnetic defect image




Technical Status

Multi-Modality Data Fusion



Experimental EM image (top) and fused data image between EM and X(γ)-ray (bottom)




Technical Status

Test Pit Testing

Test Plan:


- Testing of neutron, X(γ)-ray, and EM modality in vertical test pit
- Using multi-casing well phantom with engineered defects
- Performance characterization for each modality
- Data fusion between modalities



Schematic Sketch of Test Pit Setup



GE Oil & Gas Test Facility



Multi-Casing Well Phantom

Accomplishments to Date

- Established capabilities of high-energy modalities (neutron and X(γ)-ray backscatter based detection) through Monte Carlo N-Particle (MCNP) simulations.
- Built high- and low energy modality prototypes and performed experiments in laboratory environment.
- Conducted data analysis and data fusion between electromagnetic and X(γ)-ray modality.
- Optimized designs for all inspection modalities.



Synergy Opportunities

- Collaboration with DOE projects such as:
 - Integrated Wellbore Integrity Analysis Program for CO₂ Storage Applications - Battelle Memorial Institute
 - Wellbore and Seal Integrity - Los Alamos National Laboratory
 - Improving Science-Base for Wellbore Integrity, Barrier Interface Performance – National Energy Technology Laboratory
- Joint test well preparation with engineered structural flaws in multi-casing/multi cement annuli for field testing and performance evaluation.



Summary

- Key Findings

- X(γ)-ray modality can detect defects as small $\frac{1}{8}$ " in diameter at distance up to 3.5" past the first casing (through MCNP simulations).
- Neutron modality provides azimuthal defect resolution between defects such as air voids, cement, or high-density polyethylene.
- Electromagnetic inspection modality detects material loss in 1st casing and directional eccentricity between 1st and 2nd casing.
- Data fusion between modalities can enhance detection capabilities.



Summary

- **Lessons Learned**

- Low ultrasound frequencies (<65kHz) are required to overcome impedance mismatch between gas filled well and steel casing.

- **Future Plans**

- Finalize design optimization, build subsystem prototypes, and perform system calibration in controlled lab environment.
- Conduct performance analysis of nXis prototypes in vertical test pit (multi-casing wellbore phantom with engineered defects).
- Perform data analysis & fusion between imaging modalities.



Acknowledgement

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government of any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or of any agency thereof.



Appendix



Organization Chart



Principal Investigator

Dr. Matthias Kasten

Technical Review Team

GE Global Research

Jim LeBlanc, Technology Ldr.
Loucas Tsakalacos, Lab Manager

GE Oil & Gas

Mike Wells, Strategic COE Ldr.
Guy Mason, Engineering Manager
Taylor Shinn, Innovation Adoption Ldr.



GE Global Research

*NDE X(γ)-Ray & Neutron Detection/Imaging
Electromagnetic/Ultrasound System Integration*

Dr. Helene Climent
X-Ray Photonics

Dr. Scott Price
X-Ray Sources/Imaging

Dr. Frederick Wheeler
Data Fusion

Dr. Adrian Ivan
Detector Physics

Dr. William Ross
NDE/X-Ray, γ-Ray

Edward J. Nieters
NDE/Ultrasound

Dr. Yuri Plotnikov
NDE/Eddy Current

Dr. Sergei Dolinsky
Detector Physics



Neutron Generator Design

Brian E. Jurczyk



GE Project Team



Bill Ross



Scott Price



Helene Climent

X(γ)-Ray Team



Fred Wheeler

Data Analysis/Fusion



Ed Nieters



Yuri Plotnikov

US & EM Team



Sergei Dolinsky



Adrian Ivan



Stanislav Soloviev

Detector Team



GE Project Team



Juan-Pablo Celia



Robert Tait



Paul Chen

Design & Mechanical Engineering Team



Tom Williams



Bill Johnson

Drilling & Completion Team



Khanh Duong

Mechanical Engineering



Matthias Kasten

PI



Starfire Industries Team



Brian Jurczyk, Robert Stubbers, Matt Coventry, Aaron Krites,
and Darren Alman



Technical Review Team



Helene Climent

Principal Engineer
GE Corporate
Oklahoma City, OK



Michael Wells

Strategic COE Ldr.
GE Corporate
Oklahoma City, OK



Taylor Shinn

Innov. Adoption Ldr.
GE Corporate
Oklahoma City, OK



Guy Mason

Engineering Mgr.
GE Oil & Gas
Farnborough, GB



Jim LeBlanc

Technology Ldr.
Electronics - ETS
GE Corporate, GRC



Loucas Tsakalacos

Lab Manager
Photonics Laboratory
GE Corporate, GRC




Sandra McSurdy

Progr. Manager
NETL
U.S. Department of Energy




Gantt Chart



Legend: ◆ Milestone ◇ Decision Point ▽ Deliverable

Gantt Chart



The official program end date is September 30, 2016. However, a 6-months no-cost extension has been requested to complete all the tasks.

Bibliography

Conference Presentations/ Proceedings:

- Y.A. Plotnikov, F.W. Wheeler, S. Mandal, W.R. Ross, J.S. Price, E.J. Nieters, A. Ivan, S. Dolinsky, H.C. Climent, and A.M. Kasten, 2016, Review of Progress in Quantitative NDE Conference: Development of an Electromagnetic Imaging System for Well Bore Integrity Inspection. QNDE, July 2016, Atlanta, GA.

Accepted Conference Presentations:

- SPE Liquids-Rich Basins Conference, September 21-23, 2016, Midland, TX
- 2016 AIChE Annual Meeting, November 13-18, 2016, San Francisco, CA

Multiple patent disclosures have been filed. Journal publications will be submitted after completion of technical work.

