

# Distributed Fiber Optic Arrays: Integrated Temperature and Seismic Sensing for Detection of CO<sub>2</sub> Flow, Leakage and Subsurface Distribution

*DE-FE0012700*

**Robert C. Trautz**  
Electric Power Research Institute

**Michelle Robertson**  
Lawrence Berkeley National Laboratory



U.S. Department of Energy  
National Energy Technology Laboratory  
Mastering the Subsurface Through Technology Innovation, Partnerships and Collaboration:  
Carbon Storage and Oil and Natural Gas Technologies Review Meeting

August 1-3, 2017

# Acknowledgment and Disclaimer



- Acknowledgment: "This material is based upon work supported by the Department of Energy under Award Number DE-FE0012700."
- Disclaimer: "This presentation was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof."




# Presentation Outline

- Technical Status
- Accomplishments to Date
- Lessons Learned
- Synergy Opportunities
- Project Summary
- Appendix

# Technical Status

# Principle of Operation: Distributed Acoustic Sensing (DAS) for CO<sub>2</sub> Plume Imaging


- Light emitted into a fiber is reflected throughout the fiber's length by Rayleigh scattering
- DAS system measures the modulation of the backscattered light
- An acoustic field around the fiber exerts tiny pressure/strain changes on the fiber, resulting in changes to the backscattered light
- The DAS measures these changes by generating a repeated light pulse every 100  $\mu$ s and continuously processing the returned optical signal, thus interrogating each meter of fiber up to 10 km in length at a 10 kHz sample rate
- Unlike other methods, the system records the full acoustic signal, including amplitude and phase



**A 10 km single mode fiber becomes a high density acoustic array with 10,000 linear sensors with 1 meter spatial resolution**



# Application at SECARB Anthropogenic Test Site, Citronelle Alabama

- First integrated CO<sub>2</sub> capture, transportation and storage project on a coal-fired power station using advanced amines in the U.S.
- Southern Co. and MHI captured over 210,000 tCO<sub>2</sub>
- Denbury Resources transported, injected and stored over 114,104 tCO<sub>2</sub> in the Paluxy Formation
- Project stopped injecting and entered the Post Injection Site Care period September 1, 2014



Plant Barry, CO<sub>2</sub> pipeline and Citronelle storage site near Mobile AL

# Citronelle Offers a Unique Opportunity to Compare Seismic Methods to Monitor CO<sub>2</sub> Plume Location




Deployment of the Modular Borehole Monitoring (MBM)  
Conventional geophone array (left) and yellow flat pack  
containing the fiber optic based DAS array (right)

VSP source offset locations (stars), receiver locations  
(D9-7#2 and D9-8#2), and walk-away lines (blue and red lines)

# Comparison of Geophone to DAS Response

- 2013 implemented a large source effort (64 sweeps per shot point)
- Processed the results using adaptive stacking and spectral rebalancing to improve SNR
- DAS native measurement is strain rate
- Converted strain rate to particle velocity (Daley, et al 2015)





**Good match between geophone  
and DAS response!!**

Daley, T.M., et al. Field Testing of Modular Borehole Monitoring with Simultaneous Distributed Acoustic Sensing and Geophone Vertical Seismic Profiles at Citronelle, AL, Geophy. Prosp. (in press)


# June 2014 DAS-VSP Survey Results and Conclusions

- Migrated image →
  - Observed strong reflectors
  - Good tie to formation logs (e.g., Selma Chalk)
- Image has sufficient quality to conduct time-lapse analysis using results from the second (final) survey




# June 2014 Crosswell Survey Results

## DAS




DAS Data at 9,340 ft – Only See Random Noise, Except Some Coherent Noise Not related to sweep

## Conventional



Pixelized difference tomography results without seismic reflection overlay showing positive velocity differences in warm colors and negative differences in cool colors

# DAS Migrated Images from 2014 (left), 2015 (center) and Time Lapse Difference (right)




# Shear-Wave DAS Survey

- Collaboration between EPRI, LBNL, Silixa and the University of Texas – Austin
- UT provided their 64,000 lb Vibroseis Truck
- “T-Rex” is capable of generating compression (P) and shear (S) source waves
- One of only a few shear-wave sources in the US




# Shear-Wave DAS Survey Parameters

- Triggered DAS and conventional geophone data were collected at four site locations (VPs) with the following parameters (Figure)
  - 5–80 Hz linear sweep with 0.5 sec cosine tapers each end
    - P-mode (vertical baseplate motion)
    - SL-mode (motion radial to well D-9-8, shear-longitudinal, or inline)
    - ST-mode (motion orthogonal to well D-9-8, shear-transverse, or cross-line)
- Sweep length 16 seconds, 4 second listen time
- 32 sweeps per mode per VP (total of 96 sweeps each VP)




# Geophone Response for Source Point 2021\_3C, Correlated with the Pilot Sweep

Data were recorded at 1 kHz  
sample rate, 50-foot channel  
spacing between 6000 – 6850 ft,  
20 second records




**P-mode source  
at 2021\_3C**

# Geophone Response for Source Point 2021\_3C, Correlated with the Pilot Sweep





ST-mode source at 2021\_3C



# Non-acoustic Noise Bursts are Seen on Individual 0.25 m Channels in the Raw Data

Fiber data were recorded on a Silixa iDAS interrogator using 0.25 m spacing, 2kHz sample rate, triggered 20s records, and imaging the full fiber length.




Six traces in the 20 s record showing one magnified noise burst


Processing of this data requires editing of noise bursts and weighted stacking

# Correlated DAS data from P-mode Source Points after De-noising Pass in the Processing Flow

D-9-7\_3C




2021\_3C



DAS traces are at 2 m spacing, stack of 32 sweeps, correlated with pilot trace.

# Shear-Source DAS data from Source Point D-9-6\_3C after De-noising




Traces are at 2 m spacing, stack of 32 sweeps, correlated with pilot trace. Geophone interval is from 6000 – 6800 ft.

# Comparison of First Arrivals for Geophone vs. DAS at Source Point D-9-6\_3C

**P-mode**

**SL-mode**



DAS traces are at 2 m spacing, stack of 32 sweeps, correlated with pilot trace. No trace scaling applied.

# Accomplishments to Date

- DAS was successfully used to acquire VSP data in time-lapse mode (2012-2014)
- Wave form acquired using stacked VSP-DAS provides good match with results from conventional geophones (2015)
- Daley et al. (2015) demonstrated geophone to DAS agreement in true units
- DAS data were too noisy to allow detection of seismic waves in the crosswell configuration (2015)
- DAS was successfully used to acquire P-, SL- and ST-wave first arrivals using a triaxial vibroseis source (2016)

# Lessons Learned

- The fiber optic project has relied heavily on host sites for access to CO<sub>2</sub> wells for testing the DAS technology
- Our original DOE-funded host projects have been canceled or indefinitely delayed due to circumstances beyond our control

Field research plans need to be flexible and readily adapt to unanticipated site conditions and site host changes/schedules

# Synergy Opportunities

- Partnering with the Southeast Carbon Sequestration Partnership (SECARB), the CO<sub>2</sub> Capture Project (CCP) and the UT-Austin at the Anthropogenic Test at the Citronelle, Alabama provided an important testing ground for the DAS technology

# Project Summary

## Findings

- Fiber-optic based sensor arrays are innovative and robust
- DAS is a commercial-ready technology for monitoring CO<sub>2</sub> plume development in the VSP configuration
- Additional fiber development and testing is needed for DAS to be effective in the cross-well (broadside) configuration
- Good agreement between the geophone and DAS P- and S-wave first arrival times

## Future Plans

- Complete processing of the shear-wave data
  - Compare geophone and DAS shear-wave forms
  - Data migration to produce final seismic image
- Possible move to the Containment and Monitoring Institute's (CaMI) Field Research Station in Alberta Canada
  - Focus will be on heat-pulse monitoring using DTS



# Together...Shaping the Future of Electricity

# Appendix

# Benefit to the Program

- Program goals

- Develop and validate technologies to ensure 99 percent storage permanence.

- Benefit Statement

- The project uses Distributed Acoustic Sensor (DAS) arrays to detect and image the CO<sub>2</sub> plume using seismic methods
- Heat-pulse monitoring using Distributed Temperature Sensing (DTS) to detect vertical CO<sub>2</sub> leakage along the wellbore and flow outside of the casing
- If successful, this project will contribute to the Carbon Storage Program goal to develop and validate technologies to measure and account for 99 percent of injected CO<sub>2</sub> in the injection zones.

# Project Overview—Goals and Objectives

- **Overall objective:** Develop cost effective monitoring tools that can be used to demonstrate safe, permanent storage of carbon dioxide (CO<sub>2</sub>) in deep geologic formations.
- **Specific objectives include:**
  - Make hi-res spatial measurements of the CO<sub>2</sub> plume using permanent distributed acoustic seismic receiver arrays that utilize FO at a lower cost and with greater repeatability;
  - Monitor for CO<sub>2</sub> leakage out of the storage reservoir along wellbores and through the caprock for regulatory compliance;
  - Make hi-res measurements of the vertical distribution of CO<sub>2</sub> in the storage reservoir, allowing site operators to better manage their CO<sub>2</sub> floods and assess leakage risks;
  - Make hi-res spatial measurements of injection rates and CO<sub>2</sub> distributions in injection wells to manage and optimize EOR floods
  - Develop best available practices for deploying FO sensors in deep wells
  - Evaluate long-term robustness of FO sensor arrays in situ

# Organization Chart

- Department of Energy, NETL
  - Andrea Dunn, PM
- Electric Power Research Institute, Project Lead
  - Rob Trautz, PI
- Lawrence Berkeley National Laboratory, Geophysical & Hydrologic Modeling & Analysis
  - Tom Daley, Co-PI
  - Barry Freifeld, Co-PI
- Silixa, LLC, Fiber Optic Data Acquisition
  - Joe Greer, Co-PI





# Bibliography

- Daley, T.M., Miller, D.E., Dodds, K., Cook, P. and Freifeld, B.M. (2015), Field testing of modular borehole monitoring with simultaneous distributed acoustic sensing and geophone vertical seismic profiles at Citronelle, Alabama. Geophysical Prospecting. doi: 10.1111/1365-2478.12324