

Yuhua Duan


National Energy Technology Laboratory, U. S. Department of Energy, Pittsburgh, PA 15236, USA

Motivation

- Due to the environmental issues that the world faces today, there are significant interests to develop materials capable to capture CO₂ with optimal performances.
- Solid materials are potential candidates for CO₂ sorbents. By combining the database mining with *ab initio* thermodynamic calculation, we implemented a novel theoretical methodology to screen solid sorbents from known material databank and to synthesize new materials with improved CO₂ capture capabilities for further experimental validations.

Theoretical Methods

For the reaction of a solid to absorb CO₂ [...] are optional):



The chemical potential ($\Delta\mu$) of the reaction can be calculated as:

$$\Delta\mu(T, P) = \Delta\mu^0(T) - RT(\ln P_{\text{CO}_2} \pm \ln P_{\text{H}_2\text{O}})$$


- Intensive search for thermodynamic properties of solids from known databases and literatures. If all of them are known, obtain the better candidates by minimizing free energies based on operating conditions.
- If their thermodynamic properties are unknown, calculate by

$$\Delta\mu^0(T) \approx \Delta E^{\text{DFT}} + \Delta E_{\text{ZPE}} + \Delta F_{\text{PH}}(T) - (G_{\text{CO}_2}(T) \pm G_{\text{H}_2\text{O}}(T))$$


$$\text{Reaction Heat: } \Delta H(T, P) = \Delta\mu(T, P) + T(\Delta S_{\text{PH}}(T, P) - S_{\text{CO}_2}(T, P) \mp S_{\text{H}_2\text{O}}(T, P))$$

- where
- G_{CO_2} , S_{CO_2} , and $H_{\text{H}_2\text{O}}$ and $S_{\text{H}_2\text{O}}$ evaluated from statistical mechanics;
 - ΔE^{DFT} are calculated by density functional theory;
 - ΔE_{ZPE} , $\Delta S_{\text{PH}}(T)$ and $\Delta F_{\text{PH}}(T)$ evaluated through phonon dispersions.


High-Throughput Screening Methodology




Thermodynamic Properties of Capture Reaction




Synthesis New Sorbents to Fit Operation Needs



II. Mixture A/B Sorbents ($T_A > T_B$) using B capture CO₂ by increasing T_B



III. Doped Solid Materials to Adjust Turn-over T_i



Conclusions

- Our theoretical approach can obtain similar results as experimental measurements and can be used to identify better candidates.
- The strength of our method is to screen complex sorbent materials for which their thermodynamic properties are not available.
- Hundreds of solid materials have been investigated. Now, we are working on screening of multi-components, substituted, doped, and mixed materials to search for good CO₂ sorbents.
- By mixing/doping different solids, we can theoretically synthesize new materials which may fit the industrial operating conditions with optimal CO₂ capture performance.
- As a long time goal, we'll build a database of solid sorbents for CO₂ capture to satisfy industrial operational requirements.

Publications

- Y. Duan, et al. *Phys. Rev. B*, 79, 014301 (2009); 84(2011)104113; *Phys. Rev. Applied*, 3, 044013(2015)
- Y. Duan, B. Zhang, et al. *J. Chem. Phys.*, 133(2010)074508; 136(2012)064516
- Y. Duan, *J. Renewable Sustainable Energy*, 3(2011)013102; 4(2012)013109; *Int. J. Clear Coal Energy*, 1(2012)1-11
- F. Shi, P. Wang, Y. Duan, D. Link, B. Morreale, *RSC Advances*, 2(2012)9727-47
- Y. Duan, et al. *Phys. Chem. Chem. Phys.* 15(2013)9752-60; 15(2013)13538-58; 17(2015)22543-47
- B. Y. Li, X. F. Wang, et al. *Applied Energy*, 102(2013)1439-47; 109(2013)112-118; 161(2016)41-47
- Y. Duan, et al. *J. Phys. Chem. C*, 116(2012)14461-70; *J. Solid State Chem.* 184(2011)304-311
- X. F. Wang, et al. *Mater. Chem. A*, 1(2013)2978-82; *Energy & Fuels*, 29(2015)3780-84
- Y. Duan, et al. *ACS Applied Materials & Interfaces*, 5(2013)8670-77
- Y. Duan, et al. *Aerosol and Air Quality Research*, 14(2014)470-479; *J. Phys.: Condens. Matter*, 24(2012)325501
- K. L. Zhang, et al. *Int. J. Greenhouse Gas Control*, 12(2013)351-358; *Adv. Mater. Interfaces*, 1(2014)1400030
- P. Sanchez-Camacho, et al. *J. Phys. Chem. C*, 118(2014)19822-32; 120(2016)3798-3806; 121(2017)3455-63
- H. A. Lara-Garcia, E. Vera, et al. *RSC Advances*, 5(2015)34157-65; 6(2016)2162-70; *Chem. Eng. J.* 327(2017)783-791
- B. Alcántar-Vázquez, et al. *Ind. Eng. Chem. Res.* 54(2015)6884-92; 55(2016)9880-86.
- J. L. Chi, et al. *Int. J. Hydrogen Energy*, 39(2014)6479-91
- Y. Duan, *Sci. Lett. J.*, 3(2014)56; *Front. Environ. Sci.*, 3(2015)69
- Y. Duan, et al. *Proc. of 7th - 15th Ann. Conf. on Carbon Capture, Utilization & Sequestration*, (2008 - 2016)
- Y. Duan, et al. *Proc. of Ann. Int. Pittsburgh Coal Conf.* (2011-2015); *Proc. of 12th Int. Conf. CO₂ Utilization*, (2013)
- Y. Duan, *Proc. of AIChE Meetings* (2010, 2012, 2014, 2015); *Proc. of ACEME-15*, (New York City, 2015)
- Y. Duan, et al. *Proc. ACS National Meetings*, (2011-2016); *Proc. Int. Conf. Coal Sci. Technol.*, (University Park, 2013)

Acknowledgement

The author thanks Drs. D. C. Soreaux, B. Y. Li, X. F. Wang, K. L. Zhang, X. S. Li, D. King, B. Alcántar-Vázquez, H. Pfeiffer, P. Sanchez-Camacho, H. A. Lara-Garcia, E. Vera, J. L. Chi, L. F. Zhao, Y. H. Xiao, F. Shi, B. Zhang, D. Luebke, H. W. Pennline, J. K. Johnson, K. Parlinski, J. W. Halley, P. Singh, D. Hopkinson, W. Shi, J. Steckel, G. Richards, and M. Szymal for fruitful discussions and collaborations.