

# Initial Engineering Design of a Post-Combustion CO<sub>2</sub> Capture System for Duke Energy's East Bend Station Using Membrane-Based Technology: DE-FE0031589

**Principal Investigator: Dr. Des Dillon**  
Sr. Technical Leader

**Presenter: Dr. Abhoyjit Bhowm**  
Program Manager

**NETL CO<sub>2</sub> Capture Technology Review Meeting**  
August 16<sup>th</sup>, 2018



# Project Overview

## ■ Funding

- Federal Share: \$ 1,625,244
- Non-Federal Share: \$ 406,485
- TOTAL \$ 2,031,729

## ■ Project Performance Dates

- 04/06/2018 to 3/31/2020

## ■ DOE Project Manager

- Dr. Sai Gollakota

## ■ Project Participants

- Prime:
  - Electric Power Research Institute
- Sub-contractors:
  - Membrane Technology and Research
  - Nexant Inc.
- Site Host:
  - Duke Energy




## ■ Project Objective

- Perform an initial engineering design & cost estimate for a commercial-scale, membrane-based, post-combustion CO<sub>2</sub> capture system retrofit to Duke Energy's 600MWe coal-fired East Bend Unit.



# Background - Membrane Basic Principles

- Polymeric membrane typically operate via the solution-diffusion mechanism
- Gases dissolve into an active layer and diffuse across to the other side
- Permeation is driven by differences in partial pressures



# Background - MTR Polaris Membrane

- MTR has developed a CO<sub>2</sub> selective polymeric membrane material and module - the MTR Polaris membrane
- This provides higher CO<sub>2</sub> permeance for post combustion flue gas applications than existing polymeric membranes




Images Courtesy of MTR



# Background - Membrane Module

- Compact modular system design using high permeance membranes reduces CAPEX and overall system pressure drop
- Membranes are widely used for desalination and natural gas sweetening
- The largest existing systems are similar in scale to those required for a 550MWe coal fired power plant




Images Courtesy of MTR

# MTRs CO<sub>2</sub> Capture Development to Date



## Feasibility study (DE-NT43085)

- Sweep concept proposed
- Polaris membrane conceived



## APS Red Hawk NGCC Demo

- First Polaris flue gas test
- 250 lb/d CO<sub>2</sub> used for algae farm



## APS Cholla Demo (DE-FE5312)

- First Polaris coal flue gas test
- 1 TPD CO<sub>2</sub> captured (50 kW<sub>e</sub>)



## NCCC 1 MW<sub>e</sub> Demo (DE-FE5795)

- 11,000 hours of 1 TPD system operation
- 1 MW<sub>e</sub> (20 TPD) system operation



## Low Pressure Mega Module (DE-FE7553)

- Design and build a 500 m<sup>2</sup> optimized module



## Hybrid Capture (DE-FE13118)

- Membrane-solvent hybrids with UT, Austin



## B&W Integrated Test



Courtesy of MTR

# Advantages of the Membrane Capture Process

- Simple, passive operation with no chemical handling, emissions, or disposal issues
- Not affected by oxygen, SO<sub>x</sub> or NO<sub>x</sub>; co-capture possible
- Water use is lower than most capture technologies (recovers H<sub>2</sub>O from flue gas)
  - No steam use → no modifications to existing boiler/turbines
  - Near instantaneous response; high turndown possible
  - Very efficient at partial capture (40-60%)




# Challenges of the Membrane Capture Process

- Develop a design that will **minimize the impact** on the power plant by disrupting as little of the existing facilities as possible.
  - Also shorten the amount of downtime before the plant can resume normal operations
- Develop a design that will **minimize the cost** of each tonne of captured CO<sub>2</sub> while also maintaining the net 600 MW output of the East Bend Station.
  - This will be done by optimizing the percentage of CO<sub>2</sub> captured (~45 to 60%) and by adding a natural-gas-fired combustion turbine (CT) or possibly a combined cycle to offset the new auxiliary loads



# Partial CO<sub>2</sub> Capture with 2 Stage Membrane Process



## Preliminary Design Case for the East Bend Unit

- 2 membrane arrangement
- Aiming for 45% - 60% CO<sub>2</sub> Capture
- No boiler recycle



# Supplying the Membrane Power Requirements

- Unlike solvent PCC systems - No steam requirement, but power is required to drive the membrane systems fans, blowers, vacuum compressors pumps and CO<sub>2</sub> compression
- 4 ways to supply power will be considered:
  - New natural gas-fired simple cycle,
  - New simple cycle with heat recovery steam generator supplying steam to the coal power plant feedwater heaters
  - New combined cycle
  - Auxiliary power supplied from the existing station
- The technical and economic feasibility of adding a pipeline to supply the required amount of natural gas will be examined.
- The impacts of turning off the PCC during periods of high power demand will be evaluated (if the site has sufficient power export capacity).

# Technical Approach 1/2

- Following a data gathering task that will include a site visit to the EBS, a preliminary process design will be developed for one PCC system which captures CO<sub>2</sub> from the entire flue gas stream of the power plant.
- This preliminary design will then be subjected to a series of analyses to examine various options for minimizing the cost of CO<sub>2</sub> capture on a \$/tonne-captured basis.
- The analysis will also examine several options for providing the PCC system's auxiliary power via a CT-based power plant.
- Once an optimized process design has been identified, that design will be documented in a complete Process Design Package (PDP).

## Technical Approach 2/2

- As part of this effort a HAZOP and constructability review of the design will be conducted.
- The PDP data will be used to carry out a techno-economic analysis (TEA) that will include a +/-30% accuracy capital cost estimate as well as an estimate of the first year cost of electricity and \$/tonne cost of CO<sub>2</sub> capture for the retrofitted power plant.
- The marginal operating cost of the retrofitted plant will also be calculated and used in a unit dispatch model to predict how the retrofit will impact how often the coal plant is called on to operate.



# Project Schedule


TASK NAME:	DATES:		BUDGET PERIOD 1:												BUDGET PERIOD 2:											
	Start	End	A	M	J	J	A	S	O	N	D	J	F	M	A	M	J	J	A	S	O	N	D	J	F	M
<b>TASK 1: Project Management and Planning (EPRI lead)</b> 1.1 Project and Risk Management (EPRI) 1.2 Financial and Project Reporting (EPRI) 1.3 Technology Maturation Plan (MTR)	4/1/2018	3/31/2020																								
			M1	M2							DP															M11
						Q1			Q2			Q3			Q4					Q5			Q6			Q7
					M3																					
<b>TASK 2: Develop Design Basis document (Nexant Lead)</b>	4/1/2018	6/30/2018			M4																					
<b>TASK 3: Establish Base Case Model (Nexant Lead)</b>	7/1/2018	9/30/2018					M5																			
<b>TASK 4: System analysis of Integration options (EPRI Lead)</b> 4.1 Opimize CO2 Capture Plant Design (MTR) 4.2 Evaluate Options for Aux Power (EPRI, Nexant) 4.3 Finalize Design Configuration (EPRI , MTR, Nexant)	8/1/2018	12/31/2018																								
<b>DECISION POINT: Examine and Review Retrofit Options</b>	1/1/2019	15/1/2019												DP												
<b>TASK 5: Finalize Overall Retrofit PC Design (EPRI Lead)</b> 5.1 Design Package of the Membrane CCS System (MTR) 5.2 Design Package for BOP & Aux. Power (EPRI & Nexant) 5.3 Preliminary HAZOP Review (Nexant, Bechtel, MTR & Duke) 5.4 Constructibility Review (Nexant , Bechtel & Duke)	1/16/2019	6/30/2019																								
<b>TASK 6: Techno-Economic Analysis (EPRI Lead)</b> 6.1 Capital Cost Estimation of Integrated PCC Design (Nexant) 6.2 O&M Cost Estimation of Integrated PCC Design (Nexant, EPRI) 6.2 TEA and Dispatch Analysis (EPRI & DUKE)	7/1/2019	12/31/2019																								
<b>TASK 7: Final Report Preparation (EPRI Lead)</b>	1/1/2020	3/31/2020																							FR	

# MTRs CO<sub>2</sub> Capture Development – Current Projects



## Self-Assembly Isoporous Supports, CA (DE-FE31596)

- Improve gas transport through support layer
- Enables a reduction in membrane area
- Build and test new membrane at NCCC



## Pilot Testing at TCM, Norway (DE-FEXXXX)

- 1 MWe - advanced Polaris™ membrane
- Partial capture for low cost-of-capture
- New modular construction



## Pilot Testing at TCM, Norway (DE-FEXXXX)

- 1 MWe - Hybrid testing with TDA
- Membrane + solid sorbent for 90% capture
- Selective CO<sub>2</sub> recycle using sorbents



## Full-Scale FEED at Duke Energy's East Bend Station, KY (DE-FE31589)

- 460 MWe – using Advanced Polaris™
- Partial capture and modular membrane
- Rapid retrofit deployment



## Large-Pilot Testing at WY ITC, WY (DE-FE31587)

- Phase I – Design ~16 MWe pilot; secure host site
- Phase II – FEED and permitting
- Phase III – Fabricate, install and operate



Courtesy of MTR



# Together...Shaping the Future of Electricity

# Acknowledgement and Disclaimer



## Acknowledgement

This material is based upon work supported by the Department of Energy under Award Number DE-FE0031589.

## Disclaimer

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.