

# Integrated Oxygen Production and CO<sub>2</sub> Separation through Chemical Looping Combustion with Oxygen Uncoupling


Project DE-FE0025076

Kevin J. Whitty  
The University of Utah

2018 NETL CO<sub>2</sub> Capture Technology Project Review Meeting  
Pittsburgh, PA  
August 13-17 2018

# Project Overview

## Participants:



## Funding:

Source	University of Utah	Amaron Energy	TOTAL
DOE	\$ 1,597,665	\$ 282,655	\$ 1,880,320
Cost share	\$ 399,416	\$ 70,664	\$ 470,080
<b>TOTAL</b>	<b>\$ 1,997,081</b>	<b>\$ 353,319</b>	<b>\$ 2,350,400</b>

## Project Dates:

September 1, 2015 – March 31, 2019

## Objectives:

Advance chemical looping combustion with oxygen uncoupling (CLOU) technology to pilot scale (NETL TRL 5) through system scale-up, operation of a 200 kW process development unit, process modeling and reactor simulation





# Technology Background: Fundamental Science

## Chemical Looping with Oxygen Uncoupling (CLOU)





- Copper is one of few metals for which oxidation equilibrium ( $\text{Cu}_2\text{O}/\text{CuO}$ ) lies within CLC operating temperatures.
- $\text{Cu}_2\text{O}$  is oxidized in air reactor
- $\text{CuO}$  spontaneously releases  $\text{O}_2$  in fuel reactor due to low  $\text{O}_2$  partial pressure
- Released  $\text{O}_2$  reacts with solid coal char, converting more than 50x faster than with non-CLOU oxygen carriers



# Technology Background: Previous R&D at University of Utah



## ➤ Oxygen carrier development

- Focus on inexpensive copper-based carriers with scalable production
- Dozens of alternatives tested




## ➤ Reactor and process development

- Fundamental studies of CLOU reaction kinetics
- Lab-scale experiments of coal conversion
- Design/preparation of 200 kW PDU



## ➤ Process modeling and reactor simulation

- Aspen Plus modeling of CLC system
- Barracuda VR® modeling of integrated fluidized bed system



# Technology Background: Advantages and Challenges of CLOU

## ➤ Advantages

- CLOU can convert coal char up to 50 times faster than conventional CLC
  - Carbon conversion > 99.9% has been achieved in bench-scale tests
  - CO<sub>2</sub> capture > 99% has been achieved in bench-scale tests
  - High conversion in fuel reactor eliminates need for carbon stripper
- Fast reactions reduce reactor size and oxygen carrier inventory
- High conversion and CO<sub>2</sub> capture improves economics

## ➤ Challenges

- Operation of dual fluidized bed
  - Circulation, temperature control, particle retention
- Oxygen carrier production
  - Balance copper availability, reactivity, physical strength
- CLOU carriers are comparatively expensive
  - Physical robustness and retaining activity are especially important



# Technical Approach

## ➤ Three major research areas

1. Scale up of CLOU oxygen carrier production
2. CLOU Experiments
  - 200 kW PDU
  - 10 kW bench-scale
3. System modeling and reactor simulation

## ➤ Performance targets

- CO<sub>2</sub> capture (target min. 90%)
- CO<sub>2</sub> purity (target min. 95%)
- Coal conversion (target min. 99%)

## Work plan / Tasks

1. Project management
2. Construction of pilot-scale rotary kiln for oxygen carrier production ✓
3. Complete construction/initial testing of pilot-scale CLC system ✓
4. Evaluation of carbon conversion in CLOU environment
5. CLOU system modeling ✓
6. Production and characterization of CLOU carrier particles
7. Evaluation of CLOU performance and CO<sub>2</sub> capture at pilot scale
8. Carbon stripper design and modeling
9. Design of pilot/demo scale CLOU reactors



# Project Scope: Schedule, Milestones, Success Criteria, Risks

## ➤ Technical milestones


- 2.1 Complete pilot rotary kiln
- 3.1 Complete CLC PDU
- 3.2 Start CLOU testing
- 9.1 Large CLC system design

## ➤ Success criteria focus on PDU

- Key operation steps (\*) require that specific performance can be achieved

## ➤ Technical risks

- CLOU carrier unsuitable
  - Target lower Cu loading
- Inadequate pilot performance
  - Component redesign
- Excessive carrier attrition/loss
  - Reduce velocity, produce more carrier, find alternates
- Bed agglomeration
  - Reduce Cu content, ease into CLOU testing



# Progress and Current Status

- Oxygen carrier production scale-up
- Evaluation of carbon conversion
- Pilot system operation
- Reactor simulation



# Progress and Current Status: Scale-up of CLOU Oxygen Carrier Production

## ➤ Equipment

- 0.1 kg lab scale rotovap
- 1 kg lab scale
- 10 kg bench scale
- 100 kg pilot built (Amaron)

## ➤ Manufacture

- Wet or dry impregnation
- Support material is key
  - strong
  - inert
  - reasonable surface area
- Complexes and stabilizers
- Calcining
  - nitrate decomposition

System	Type	Capacity	Heating	Max T	Length	Diam
RV-1	Rotary evap	1 kg	Water bath	95°C	n/a	0.15 m
RK-1	Rotary kiln	1 kg	Elec Inductive	800°C	0.15 m	0.1 m
RK-10	Rotary kiln	10 kg	Elec radiative	350°C	0.8 m	0.2 m
RK-100	Rotary kiln	100 kg	Natural gas	600°C	1.4 m	0.4 m



RK-1 lab-scale induction kiln



RK-100 oxygen carrier production kiln



RK-10 bench-scale rotary kiln







# Progress and Current Status: Improvement of CLOU Oxygen Carriers

## ➤ Status


- Over 65 carriers tested
- Baseline support: SiC
  - cheap but poor Cu distribution
- New supports:  $\text{SiO}_2$ ,  $\text{MgAl}_2\text{O}_4$ 
  - also with stabilizers
- Test batches of 50 kg produced
- Good cyclability in small fluid bed

## ➤ Characterization


- TGA: oxygen loading/rates
- BET: surface area
- SEM: morphology, Cu distribution
- Crush strength
- Lab-scale fluidized bed for long-term performance in a cycling fluidized bed reactor



Silica support






1 addition





1 addition calcined



2 additions calcined






Lab-scale fluidized bed system



# Support Material Cost vs. Performance



Metric	SiC	Ilmenite	Engineered SiO <sub>2</sub>
Strength	++	+	+
Sphericity	--	-	++
Porosity	--	--	++
Internal surface area	--	--	++
Cu loss (attrition)	-	-	+
Uniformity	-	-	+
Impregnability	--	-	++
Cost	+	++	--




# Advances in Impregnation Precursor

## SiO<sub>2</sub> Support




Copper Nitrate  
(1M)  
20wt% CuO



TGA curve (900°C)



Tetraamine  
Copper Nitrate  
(0.45M)  
32wt% CuO



# Select Oxygen Carriers

Support	CuO loading (wt%)	Preparation Method	BET Area (m <sup>2</sup> /g)	Attrition Rate (%/h)	Agglomeration Temperature (°C)
Titania (Poland)	43	Mechanical mixing	NA	1.3	850
Zirconia (Chalmers)	43	Freeze Granulation	NA	1.5	925
SiC	20	WI (1M) 4 additions	<0.1	-	925
Silica	19	WI, CN, 2 additions	160	0.5	875
Silica	23	WI, CN, 3 additions	219	-	950
Silica	38	WI, TACN, 5 additions	270	0.3	>975






# Progress and Current Status

- Oxygen carrier production scale-up
- **Evaluation of carbon conversion**
- Pilot system operation
- Reactor simulation




# Evaluation of Carbon Conversion

- 9 possible pathways for carbon
  - 6 to  $\text{CO}_2$
- Evaluate conversion mechanism in 10 kW reactor
  - Steam vs.  $\text{N}_2$
  - Coal vs. char
  - CLOU vs. non-CLOU
  - Fuel particle size




# Carbon Conversion: CLOU vs non-CLOU

Fraction of carbon (400- micron coal) converted to gaseous species at 900 C, fluidizing in steam.



Carbon conversion at 90 seconds of the 400-micron char at 900 C, fluidizing in steam.



☐ Unconverted (CO, CH<sub>4</sub>)

■ Converted (CO<sub>2</sub>)


- CLOU more effective at converting carbon in coal
- Less unconverted gases when using a CLOU carrier




# CLOU Carbon Conversion

## Influence of Temperature and Fuel Particle Size

Carbon conversion at 90 seconds of the 400-micron char fluidizing in steam.



Carbon conversion of char at 90 seconds at 900 C fluidizing in steam.



- Carbon conversion increases at elevated temperatures.
- Smaller coal particles convert at a faster rate than the larger particles.
- Smaller coal particles exit the reactor more readily.



# Progress and Current Status

- Oxygen carrier production scale-up
- Evaluation of carbon conversion
- **Pilot system operation**
- Reactor simulation and scale-up






# Progress and Current Status: PDU Operation

- Preliminary testing
  - Cold flow circulation rates
  - Hot flow circulation rates
  - Ilmenite as oxygen carrier
- Operation progression
  - CLC of natural gas
    - ilmenite
    - Cu-on- $\text{Al}_2\text{O}_3$
  - iG-CLC of coal
    - ilmenite
    - Cu-on- $\text{Al}_2\text{O}_3$
  - CLOU of coal
    - CLOU carrier



# Analysis of PDU Performance: Input and Output Streams




1	Burner Air	(AR)
2	Natural Gas	(AR)
3	Fluidizing Air	(AR)
4	O <sub>2</sub>	(AR)
5	Burner Air	(FR)
6	Natural Gas	(FR)
7	Steam	(FR)
8	Coal	(FR)
9	Fluidizing Gas- Loop Seal	(FR to AR)
1	Horizontal	
2	Vertical	
10	Fluidizing Gas- Loop Seal	(AR to FR)
1	Horizontal	
2	Vertical	
11	Fluidizing Gas- Loop Seal	(FR recycle)
1	Horizontal	
2	Vertical	
12	Propane/ Natural Gas	(AR)
13	Propane/ Natural Gas	(FR)
14	Pressure Tap Purge	(AR)
15	Pressure Tap Purge	(FR)
16	H <sub>2</sub> O + Bed Material	(AR)
17	Elutriated Bed Material	(AR)
18	Exiting Gases	(AR)
19	H <sub>2</sub> O + Bed Material	(FR)
20	Elutriated Bed Material	(FR)
21	Exiting Gases	(FR)
22	Air	(AR)
23	Gas Sample	(AR)
24	Gas Sample	(FR)
25	Air	(FR)




# Data Acquisition over 1 Hour

## Fuel Reactor



## Air Reactor






# Progress and Current Status: PDU Operational Experience

## ➤ Status

- Construction complete
- Shakedown complete
  - Gas flow + preheat
  - Controllable coal feed
  - Circulation rates > 10 ton/hr
- Over 800 hours of hot circulation
- Temps to 1700°F achieved
- Operators comfortable



## ➤ Challenges

- Preheat
  - electric, burners, propane, nat gas
- Cyclones and bed loss
  - Geometry vs wall roughness
  - Loop seal operation
  - Loop seal sensors
  - Particle size
- “Normal” things
  - Leaks, etc.



# Progress and Current Status: Oxygen Carrier for PDU

- Oxygen carriers tested to date
  - Ilmenite (non-CLOU)
  - CuO on silicon carbide
  - CuO on ilmenite
- Experience with low-cost CLOU carriers
  - Unacceptable Cu loss
  - Agglomeration tendency
- Future testing will be with superior CLOU carrier
  - CuO on engineered  $\text{SiO}_2$  support
  - Good performance in 10 kW unit
    - Reactivity
    - No agglomeration
    - “Fluidizability”
  - Downside is high cost
  -




# Progress and Current Status

- Oxygen carrier production scale-up
- Evaluation of carbon conversion
- Pilot system operation
- **Reactor simulation and scale-up**



# Progress and Current Status: Process Modeling and Simulation

- Experimental modeling
  - Plexiglas cold flow system
  - Scaled properly to represent PDU
  - 60% scale
  - Air for fluidization
  - Glass beads
  - Pressure profiles
  - Circulation rates
- Computational simulation
  - CPFD Barracuda VR<sup>®</sup>




Cold-flow model of UofU PDU



# Progress and Current Status: Chemical Looping Reactor Simulation

- Models of 10 kW bench-scale, 200 kW pilot-scale reactors, and cold-flow unit
- Simulations include
  - hydrodynamics
  - heat transfer
  - Chemistry/kinetics
    - Oxygen carrier
    - Coal combustion
    - Gas phase
- Understanding from simulations valuable for interpreting behavior of pilot-scale system



# Progress and Current Status: Significant Accomplishments

- **Successful scale-up of CLOU oxygen carrier production**
  - Can now produce enough material for PDU operation
  - Material with up to 20% CuO loading produced
- **Successful commissioning of PDU**
  - All systems now function properly
  - Measured oxygen carrier circulation rates exceed design
  - 800+ hours of hot operation with circulation
  - Stable coal feeding achieved
- **Successful development of PDU simulation model**
  - Incorporation of kinetics for oxygen carrier reactions
  - Incorporation and improvement of coal combustion reaction kinetics
  - Over 55 different conditions have been simulated, each with at least 60 seconds of operation



# Future Plans

## ➤ This project

- Continue improving CLOU carrier performance
  - Improve physical and chemical stability
  - Target 40+ % CuO to increase load
- Parametric testing of PDU with CuO (CLOU) carrier and coal
  - Vary coal, coal particle size, air reactor flow rate (circulation rate),
  - Measure CO<sub>2</sub> capture, CO<sub>2</sub> purity, fuel conversion, overall performance
- Advance computational simulation
  - Validate simulation of PDU with operational data
  - Simulate larger (e.g. 10 and 100 MW) reactors

## ➤ Future development

- Continued operation and experience with PDU
- Evaluate PDU performance with different oxygen carriers
- Pursue opportunities for larger pilot (3-10 MW) system



# Acknowledgments

- This material is based upon work supported by the Department of Energy under Award DE-FE0025076.
- University of Utah Chemical Looping team
- Amaron Energy

Disclaimer: This presentation was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.



Please join us in 2018 at the  
5<sup>th</sup> International  
Chemical Looping Conference  
Park City, Utah  
24-27 September 2018

Chemical  
**Looping**  
2018

